

NUMBER OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
TRANSPORTER	OIL GAS
PROBATION OFFICE	
OPERATOR	

(Form C-102)
(Revised 7/1/53)

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

strict Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

November 20, 1964
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Aztec Oil & Gas Company Atlantic State Well No. 1 in E
(Company or Operator) (Unit)
SW $\frac{1}{4}$ NE $\frac{1}{4}$ of Sec. 21, T. 17-S, R. 36-E, NMPM., Double A Abo Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

We propose to plug this well in the following manner:

1. Load hole with drilling mud.
2. Spot 10 sacks cement across perforations at 9362-9400.
3. Cut off $4\frac{1}{2}$ " casing at 8540.
4. Spot 25 sacks cement at $4\frac{1}{2}$ " casing stub.
5. Spot 25 sacks cement at Clearfork (7828).
6. Spot 25 sacks cement at Glorieta (6800).
7. Spot 25 sacks cement at San Andres (5143).
8. Spot 25 sacks cement at Base of 8-5/8" casing (4070).
9. Cut off 8-5/8" casing at 1753.
10. Spot 25 sacks cement at 8-5/8" casing stub.
11. Spot 25 sacks cement at Base of 13-3/8" casing (304).
12. Spot 10 sacks cement at surface.
13. Place regulation marker and clean-up location.

Approved....., 19.....
Except as follows:

Aztec Oil & Gas Company
Company or Operator

By.....

Approved
OIL CONSERVATION COMMISSION

Position..... District Superintendent
Send Communications regarding well to:

By.....

Name..... Aztec Oil & Gas Company

Title.....

Address..... P. O. Box 837, Hobbs, New Mexico