

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL	X	REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

.....**January 5, 1953**.....**Artesia, New Mexico**.....
(Date) (Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Carper Drilling Co., Inc......**Carper-Emery**.....
(Company or Operator) (Lease)
Bosworth Drilling Co......, Well No. **1**..... in the **NW** 1/4 **SW** 1/4 of Sec. **28**.....
(Contractor)
T. **17 S.**, R. **36 E.**, NMPM., **Wildcat**..... Pool, **Lea**..... County.

The Dates of this work were as follows:.....**January 4, 1953**.....

Notice of intention to do the work (was) (~~was not~~) submitted on Form C-102 on.....**January 5**....., 19**53**,
(Cross out incorrect words)

and approval of the proposed plan (was) (~~was not~~) obtained. **By telephone conversation between Roy Yarbrough & Marshall Rowley 1-3-53**

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

This well was plugged as follows: Total depth: 10,197'

9316' - Baker bridging plug run by Lane Wells
9300' - 3 Sax cement dumped by Lane Wells
9200' - 10 sax cement - should fill 50' in 6 1/2" hole
6900' - 10 " " " " " "
3700' - 10 " " - where 7" casing was parted
3140' - 10 " " - base of the salt
2150' - 10 " " - top of salt @ 2150' - this plug spotted in 8 5/8" casing since we did not attempt to pull

0 - 10 sax cement to seal top of hole and place a regulation marker.
Location will be cleaned and leveled when the rig is moved. Cementing done by Halliburton.

Witnessed by.....**Marshall Rowley**.....**Carper Drilling Co., Inc.**.....**Vice-Pres.**.....
(Name) (Company) (Title)

Approved: **OIL CONSERVATION COMMISSION**

Roy Yarbrough.....
(Name)
.....
(Title) (Date)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name.....**Marshall Rowley**.....
Position.....**Vice-Pres.**.....
Representing.....**Carper Drilling Co., Inc.**.....
Address.....**Artesia, N. M.**.....