

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

## MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	<b>X</b>	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Artesia, New Mexico

January 5, 1953

(Place)

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the **Carper-Emery****CARPER DRILLING CO., INC.**

(Company or Operator)

Well No. **1** in **L**

(Unit)

NW  $\frac{1}{4}$  SW  $\frac{1}{4}$  of Sec. **28**, T. **17 S**, R. **36 E**, NMPM., **Wildcat** Pool

(40-acre Subdivision)

**Lea**

County.

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

We propose to plug and abandon this well from present total depth of 10,197' as follows. A Baker bridging plug will be set @ 9316'. and 3 sax of cement will be dumped on top of plug. Cement should fill back to 9300'. After testing, we will pump 10 sax cement thru open ended drill pipe @ 9200'. Drill pipe will then be ~~pk~~ pulled up to 6900' and a 10 sack cement plug will be spotted. We will pull the drill pipe and cut the 7" casing @ approximately 3700'. After the casing is pulled, we will spot a 10 sack cement plug where the pipe is parted, spot a 10 sack cement plug @ 3140' base of the salt and a 10 sack cement plug @ 2150' which will be 23' from the bottom of the 8 5/8" casing. Top of the salt was 2150'. We will not attempt to pull the 8 5/8" casing. A regulation marker will be cemented in the top of the 8 5/8" casing. Location will be cleaned and leveled.

(The above work discussed in telephone conversation between Roy Yarbrough & Marshall Rowley - 1-3-53)

Approved....., 19.....  
Except as follows:**CARPER DRILLING COMPANY, INC.**

Company or Operator

By *Marshall Rowley*Position **Vice-Pres.**

Send Communications regarding well to:

Approved  
OIL CONSERVATION COMMISSIONBy *Roy Yarbrough*

Title.....

Name **Carper Drlg. Co., Inc.**Address **Artesia, N. M.**