

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO RE-DRILL OR PLUG BACK TO A DIFFERENT RESERVOIR.
SEE APPLICATION FOR PERMIT - 11-1001 (C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
2. Name of Operator Getty Oil Company	5. State Oil & Gas Lease No.
3. Address of Operator P. O. Drawer DD, Levelland, Texas 79336	7. Unit Agreement Name
4. Location of Well UNIT LETTER <u>D</u> <u>660</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>4</u> TOWNSHIP <u>17-S</u> RANGE <u>37-E</u> N.M.P.M.	8. Form or Lease Name State "U"
	9. Well No. <u>1</u>
	10. Field and Pool, or Wildcat Lovington Paddock
15. Elevation (Show whether DF, RT, CR, etc.) 3804' D.F.	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

The subject well ceased to produce oil. It was plug and abandoned by the following procedure.
Work began on 11-14-83 and was completed on 11-21-83.

- Plug 1: Set Halliburton E-Z drill retainer at 6241' and circulated hole with 9# gel. Stung in and squeezed 120 sx Class "C" below retainer, pulled out, dumped 4 sx on top of retainer.
- Plug 2: Perfed 4 shots at 5000'. Set EZ drill retainer at 4761'. Could not pump into holes. NMOCC ok'd 100' plug on top of retainer so spotted 25 sx.
- Plug 3: Perfed 4 shots at 2050'. Decided to recover 8 5/8" csg. Cut casing at 1995' and 1911'. Did not come free. Abandoned recover attempts. Circulated hole with 9# gel and spotted 50 sx Cl "C" plug from 2015 to 1837'.
- Plug 4: Perfed 4 shots at 350. Set 8 5/8" retainer at 337' and pumped 200 sx Class "C", circulated to surface.
- Surface Plug: Cut off casing. Lay 10 sxs. Plug and installed dry hole marker.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED F. L. Dietrich TITLE Area Engineer DATE 11-29-83

REMOVED BY Ronald M. Calhoun TITLE OIL & GAS INSPECTOR DATE FEB 23 1984

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED
DEC 1 - 1983
S.C.D.
HOUS OFFICE