NEW MEXICO OIL CONSERVATION COMMISSION

Santa, Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

OTICE O		TION TO TE	ST CASING		F INTENTION IICALLY TREAT		TOR	
GOTICE OF INTENTION TO CHANGE PLANS				NOTICE O	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING			
OTICE O	F INTENT	ION TO RE	PAIR WELL					
OTICE O	F INTENT	TION TO DE	EPEN WELL	NOTICE O	F INTENTION	TO PLUG	WELL	Y
	Hobbs. N					Oct. 12, 1939		
				Place			Date	
		COMMISSI	ON,					
nta Fe, I ntlemen:	New Mexic	co.					4	
	s a notice o	of intention to	do certain work a	as described below	at the			
medan (Oil Corp)e		r Caylor				
compan.	.,,			, N. M. P. M.,				
	·-		County.	, IV. MI. F. MI.,				Field,
	Lea			PROPOSED PLA				
Ŧ	FOLLOW	INSTRUCTIO	NS IN THE RUI	LES AND REGULA	TIONS OF THE	e commi	SSIUN	
Plan 11 brid	n to pul dge in t	1 the cas:	ing and plug to the 52" can	the above descr asing and cemer	ribed well o	n or ab five sa	out Oc cks of	t. 15, 1 cement.
idge in ment. d erect	n the bo Bridge t a mark	ttom of thin the books er.	ne 8 5/8" cast ttom of the 13	ing at 3154 fee 3° casing at 29	et and cemen 90 feet and	t a plu cement	g of (to the	10) saci surface
idge in ment. d erect	n the bo Bridge t a mark	ttom of thin the books er.	ne 8 5/8" cast ttom of the 13	ing at 3154 fee	et and cemen 90 feet and	t a plu cement	g of (to the	10) saci surface
idge in ment. d erect	n the bo Bridge t a mark	ttom of thin the books er.	ne 8 5/8" cast ttom of the 13	ing at 3154 fee 3° casing at 29	et and cemen 90 feet and	t a plu cement used i	g of (to the	10) saci surface ing the
idge in ment. d erect	n the bo Bridge t a mark	ttom of thin the books er.	ne 8 5/8" cast ttom of the 13	ing at 3154 fee 3° casing at 29	et and cemen 90 feet and f the cement	t a plu cement used i	g of (to the n sett	10) saci surface ing the
idge in ment. d erect	n the bo Bridge t a mark 11 shoot	ttom of the horizon. the casin	ne 8 5/8" cast ttom of the 13 ng strings off	ing at 3154 fee 5" casing at 29 I at the top of	et and cemen 90 feet and f the cement	t a plu cement used i	g of (to the n sett 4 1937	10) saci surface ing the
idge in ment. d erect Willpe.	h the bo Bridge t a mark 11 shoot	ttom of the horizon. the casin	ne 8 5/8" cast ttom of the 13	ing at 3154 fee 5" casing at 29 I at the top of	et and cemen 90 feet and f the cement	cement used i	g of (to the n sett 4 1937	10) saci surface ing the
idge in ment. d erect Will pe.	h the bo Bridge t a mark 11 shoot	ttom of the horizon. the casin	ne 8 5/8" cast ttom of the 13 ng strings off	ing at 3154 fee 5" casing at 29 I at the top of	et and cemen 90 feet and f the cement The cement Company or	cement used i	g of (to the n sett	10) saci surface ing the
idge in ment. d erect Willpe.	h the bo Bridge t a mark 11 shoot	ttom of the horizon. the casin	ne 8 5/8" cast ttom of the 13 ng strings off	ing at 3154 fee To casing at 23 If at the top of Sar By Position	et and cemen 90 feet and f the cement	t a plu cement used i	g of (to the n sett	10) saci surface ing the
idge in ment. d erect Will pe.	h the bo Bridge t a mark 11 sh oot	ttom of the horser. the casin	ne 8 5/8" cast true 13 ng strings off	Sar By Position Send	et and cemen 90 feet and f the cement medan 011 Co Company or communications	cement used i	g of (to the n sett	10) saci surface ing the
idge in ment. d erect Will pe.	h the bo Bridge t a mark 11 shoot	ttom of the in the bottom. the casin	ne 8 5/8" cast ttom of the 13 ng strings off	sar By Position Send	et and cemen 90 feet and f the cement The communications communications	cement used i	g of (to the n sett	10) saci surface ing the
idge in ment. d erect Will pe.	h the bo Bridge t a mark 11 shoot	ttom of the horser. the casin	ne 8 5/8" cast ttom of the 13 ng strings off	sar By Position Send	et and cemen 90 feet and f the cement medan 011 Co Company or communications	cement used i	g of (to the n sett	10) saci surface ing the