NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELL

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-offs, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate	nature	of	report	by	checking	below:
----------	--------	----	--------	----	----------	--------

REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON REPAIRING WELL
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL	REPORT ON PULLING OR OTHERWISE ALTERING CASING
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON DEEPENING WELL
REPORT ON RESULT OF PLUGGING OF WELL	
	Hobbs, New Mexico Aug. 22 1959
OIL CONSERVATION COMMISSION,	Place
Santa Fe, New Mexico.	DUPLICATE
Gentlemen:	
	C. S. Caylæ Well No. 1 in the
CNV NE of Sec. 6	T. 17E , R. 378 , N. M. P. M.,
South Lovington Field,	County
The dates of this work were as follows:	Aug. 11, 1939
	ubmitted on Form C-102 on Aug. 12, 19 39 otained. (Cross out incorrect words)
	,
After allowing cement to set a casing shut-off in 13" OD cast	ORK DONE AND RESULTS OBTAINED 48 hrs, drilled plug and tested for ing set by Halliburton Process at
After allowing cement to set a casing shut-off in 13" OD cast 336! - casing shut-off tested NOTE: Through error th	48 hrs, drilled plug and tested for ing set by Halliburton Process at OK and drilled ahead.
After allowing cement to set a casing shut-off in 13" O' cast 336! - casing shut-off tested NOTE: Through error that time this wor	48 hrs, drilled plug and tested for ing set by Halliburton Process at OK and drilled ahead. his report was not substited AUG 2 3 1939
After allowing cement to set a casing shut-off in 13" O' cast 336! - casing shut-off tested NOTE: Through error that time this wor	48 hrs, drilled plug and tested for ing set by Halliburton Process at OK and drilled ahead.
After allowing cement to set a casing shut-off in 13" O" casing shut-off tested NOTE: Through error that time this work Witnessed by Chas Kemnitz	48 hrs, drilled plug and tested for ing set by Halliburton Process at OK and drilled ahead. his report was not substited AUG 2 3 1939 American Drig. Co. HOBBS OFFICE are Title
After allowing cement to set casing shut-off in 13" O' casing shut-off in 13" O' casing shut-off tested NOTE: Through error that time this work Witnessed by Chas Kemnitz Name Subscribed and sworn to before me this	Als hrs, drilled plug and tested for ing set by Halliburton Process at OK and drilled ahead. his report was not substited Aug 23 1939 American Drig. Co. HOBBS OFFICE at Title I hereby swear or affirm that the information given above is true and correct.
After allowing cement to set casing shut-off in 13" O' casing shut-off in 13" O' casing shut-off tested NOTE: Through error that time this work Witnessed by Chas Kemnitz Name Subscribed and sworn to before me this Against 19	Als hrs, drilled plug and tested for ing set by Halliburton Process at OK and drilled ahead. his report was not substited Aug 23 1939 American Drig. Co. HOBBS OFFICE at Title I hereby swear or affirm that the information given above is true and correct.
After allowing cement to set casing shut-off in 13" O' casing shut-off in 13" O' casing shut-off tested NOTE: Through error that time this work Witnessed by Chas Kemnitz Name Subscribed and sworn to before me this	Als hrs, drilled plug and tested for ing set by Halliburton Process at OK and drilled ahead. his report was not substited Aug 23 1939 American Drig. Co. HOBBS OFFICE at Title I hereby swear or affirm that the information given above is true and correct.
After allowing cement to set casing shut-off in 13" O' casing shut-off in 13" O' casing shut-off tested NOTE: Through error that time this work Witnessed by Chas Kemnitz Name Subscribed and sworn to before me this Against 19	48 hrs, drilled plug and tested for ing set by Halliburton Process at OK and drilled ahead. his report was not substited AUG 23 1939 American Drig. Co. HOBBS OFFICE an Title I hereby swear or affirm that the information given above is true and correct. Name Position Position Representing Skelly Office.
After allowing cement to set casing shut-off in 13" O' cas: 336' - casing shut-off tested NOTE: Through error that time this work Witnessed by Chas Kemnitz Subscribed and sworn to before me this day of August 19	A8 hrs, drilled plug and tested for ing set by Halliburton Process at OK and drilled ahead. his report was not substited AUG 23 1939 American Drlg. Co. HOBBS OFFICE are Title I hereby swear or affirm that the information given above is true and correct. Name Position District Supt
After allowing cement to set casing shut-off in 13" O' cas: 336' - casing shut-off tested NOTE: Through error that time this work Witnessed by Chas Kemnitz Name Subscribed and sworn to before me this Aday of August 19	A8 hrs, drilled plug and tested for ing set by Halliburton Process at OK and drilled ahead. his report was not substited AUG 23 1939 American Drig. Co. HOBBS OFFICE AT Title I hereby swear or affirm that the information given above is true and correct. Name Position Position Representing Skelly Oil Co. Company or Operator

Title