
TL JONSERVATION COMMISSION

Santa Fe, New Mexico



Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

REPORT ON BEGINNING DRILLING OPERA-			
110118	REPORT	ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEM- ICAL TREATMENT OF WELL		ON PULLING OR OTHERWISE ERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X REPORT	ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			
Hobbs,	New Mexico	June 6, 1946	
OIL CONSERVATION COMMISSION, SANTA FE, NEW MEXICO. Gentlemen:			
Following is a report on the work done and the resul			
Skelly Oil Company C.	S. Caylor	Well No	in the
- · · · · -	Lease		
NW NE NE of Sec.	T. 178	, R, 1	V. M . P. M.,
Lovington Field,	L	Dg	County.
The dates of this work were as follows:			
Notice of intention to do the work was (************************************	bmitted on Form C-10	2 on June 3	10 AR
7-5/8" OD casing on bottom	with 500 sack	nd cemented string of is. Used Halliburton	1
7-5/8" OD casing on bottom Process. Cement circulated Drilled plug and casing shu	with 500 sach back to suring t-off tested	rs. Used Halliburton Race. Let set 72 how okay. Now drilling	rs. ahead.
7-5/8" OD casing on bottom Process. Cement circulated Drilled plug and casing shu	with 500 sach back to suring t-off tested	ace. Let set 72 how okay. Now drilling	irs. ahead.
7-5/8" OD casing on bottom Process. Cement circulated Drilled plug and casing shu	th 500 sach back to surfit off tested Coats & Fosts Coats & Fosts I hereby sweat is true and cor Name	cs. Used Halliburton (ace. Let set 72 hor okay. Now drilling priller mpany r or affirm that the information	irs. ahead.
7-5/8" OD casing on bottom Process. Cement circulated Drilled plug and casing shu Witnessed by B. T. Rushing, Name Subscribed and sworn before me this Aday of June, 19	Legister of tested Coats & Foste C	r or affirm that the information process. Supt.	irs. ahead.