

NEW
DUPLICATE

MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

RECEIVED
MAY 21 1946

NOTICE OF INTENTION TO DRILL

Notice must be given to the Oil Conservation Commission or its proper agent and approval begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

Hobbs, New Mexico

May 18, 1946

Place

Date

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico,

Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as

SKELLY OIL CO.

C. S. Caylor

Well No. 2 in CNW NE NE

Company or Operator

Lease

of Sec. 6, T. 17S, R. 37E, N. M. P. M., Lovington Field, Lea County.

The well is 330 feet (SE) (S.) of the North line and 990 feet (W.) of the East line of Section 6-

(Give location from section or other legal subdivision lines. Cross out wrong directions.)

If state land the oil and gas lease is No. Assignment No.

If patented land the owner is

Address

If government land the permittee is

Address

The lessee is Skelly Oil Co.

Address Tulsa, Oklahoma

AREA 640 ACRES

LOCATE WELL CORRECTLY

We propose to drill well with drilling equipment as follows:

Rotary tools from top to total depth.

The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission is as follows:

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Sacks Cement
15"	15" OD	40#	Conductor	20'	Cemented	20 -dumped
10 1/2"	7-5/8"	26#	New	2100'	Cemented	375
6 1/2"	5-1/8"	17#	New	4600'	Cemented	200

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about 4635' feet.

Additional information: Approximately 20' of 15" OD casing will be set as conductor and cemented with 20 sz cement. In cementing all the above strings sufficient time will be allowed for cement to thoroughly set before drilling plug and testing for casing shut-off.

Approved MAY 23 1946, 19

Sincerely yours,

except as follows:

1 1/2" pipe set at 2100 ft should be cemented back to 300 ft to protect fresh water

SKELLY OIL COMPANY

Company or Operator

By

Position District Supt.

Send communications regarding well to

Name SKELLY OIL COMPANY

Drawer D

Address Hobbs, New Mexico

OIL CONSERVATION COMMISSION,

By

Ray Garbarran

Title

Oil & Gas Inspector

