

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to Oil Conservation Commission, Santa Fe, New Mexico, or its proper agent not more than twenty days after completion of well. Follow instructions in the Rules and Regulations of the Commission. Indicate questionable data by following it with (?). SUBMIT IN TRIPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Skelly Oil Company

C. S. Cayler

Company or Operator
Well No. 3 in NW NE of Sec. 6, T. 17S

R. 37E, N. M. P. M., Livingston - Abq. Field, Lea County.

Well is 330 feet south of the North line and 2310 feet west of the East line of Section 6 - 17S - 37E

If State land the oil and gas lease is No. _____ Assignment No. _____

If patented land the owner is C. S. Cayler, Address Livingston, New Mexico

If Government land the permittee is _____, Address _____

The Lessee is Skelly Oil Company, Address Tulsa, Oklahoma

Drilling commenced May 5 1952 Drilling was completed June 17 1952

Name of drilling contractor Sharp Drilling Company, Address Midland, Texas

Elevation above sea level at D.F. 3820 feet.

The information given is to be kept confidential until not confidential 19____

OIL SANDS OR ZONES

No. 1, from 8360 to 8414 No. 4, from _____ to _____

No. 2, from _____ to _____ No. 5, from _____ to _____

No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet.

No. 2, from _____ to _____ feet.

No. 3, from _____ to _____ feet.

No. 4, from _____ to _____ feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	THREADS PER INCH	MAKE	AMOUNT	KIND OF SHOE	CUT & FILLED FROM	PERFORATED FROM	TO	PURPOSE
13 3/8	48#	8R	Nat'l	224					
8 5/8	24#	8R	Nat'l	2435					
8 5/8	32#	8R	Youngstown	923					
5 1/2	17#	8R	Republic	8495			8360	8414	
			J&L						
Tubing	-	2" NUE	Republic		4.7#	J-55	8439'	set at 8410'	

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
18	13-3/8	240	240	Halliburton		
12-1/4	8-5/8	3356	800	"		
7-7/8	5-1/2	8435	800	"		

PLUGS AND ADAPTERS

Heaving plug—Material _____ Length _____ Depth Set _____

Adapters—Material _____ Size _____

RECORD OF SHOOTING OR CHEMICAL TREATMENT

SIZE	SHELL USED	EXPLOSIVE OR CHEMICAL USED	QUANTITY	DATE	DEPTH SHOT OR TREATED	DEPTH CLEANED OUT
		Mud acid	800 gals.	6/22/52	8360-8414	
		15% acid	2000 gals.	6/22/52	8360-8414	

Results of shooting or chemical treatment Flowed Oil.

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 8435 feet, and from _____ feet to _____ feet.

Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet.

PRODUCTION

Put to producing June 23 1952

The production of the first 24 hours was 751 barrels of fluid of which 100 % was oil; _____ %

emulsion; _____ % water; and _____ % sediment. Gravity, Be API 40 Corr.

If gas well, cu. ft. per 24 hours _____ Gallons gasoline per 1,000 cu. ft. of gas _____

Rock pressure, lbs. per sq. in. _____

EMPLOYEES

Chester King, Driller _____, Driller

J. E. Aldridge, Driller _____, Driller

FORMATION RECORD ON OTHER SIDE

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Hobbs, New Mexico July 7, 1952

Place _____ Date _____

Name _____

Position Dist. Supt.

Representing Skelly Oil Company

Company or Operator.

Address Box 38, Hobbs, New Mexico

