## NEW MEXICO OIL CONSERVATION COMMISSION NOTICE OF INTENTION TO DRILL

			1 MAY	5 1952			
	See Rules	3 101 and 1104.	1	-			
If changes in the proposed pla the sender. Submit this notice	n are considered advisable, in triplicate. One copy will	a copy of this noti be returned followi	ng approver   OIF OR HOPER	will be returned to ATION SUMMARY ATION SUMMARY AT SECOND AT A SEC			
	Hobbe 1	lew Mexico		2, 1952			
	moon) :	Place		Date			
		a lilling of a	well to be known as				
Notice hereby is given that	it is our intention to comme	ice the drilling of a	wen to be known as	27.// 200//			
Skelly Oil Company	C.S. Car	lor	well No	in NW/A RA/A			
Company	or Operator	Lease	Tan	County			
of Sec. 6, T. 178	, R, N. M., P.	W TOATURCOU-VE	Pool,	County			
	The well is	feet from (	N.) Ine and 2310	feet from			
N	(E.) M.) line of the al	nove section.					
103			out wrong directions.)				
				•			
	If state land the oil and	gas lease is No	Assignment N	0			
6	If patented land the ow	ner is C.S.	aylor	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,			
	Address Lovington, New Mexico						
<del>┠╌┤╌╎╌╎╴╏┈╎╸┤╸</del> ┦	Te	normittee is		***************************************			
	If government land the	permittee is					
	Address	1 O.1.1		••••			
	The lessee is	TA OIT COMPANY	7				
AREA 640 ACRES	Address Tuls	a, Oklahoma					
LOCATE WELL CORRECTLY	We propose to drill well with drilling equipment as follows: Rotary 20018						
	from surface to t	otal depth.					
The status of a bond for this w	ell in conformance with Rule	101 of the General	Rules and Regulations of t	he Commission is a			
follows:		• · · · · · · · · · · · · · · · · · · ·					
We propose to use the following	ng strings of casing and to la	and or cement them	as indicated:				
We brobose to and the		ew or	Landed or	Sacks			

Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Sacks Cemen
18"	13-3/8"	44.5	New	3001	Cemented	300
12-1/4"	9-5/8=	36	New	34001	Cemented	1500
7-7/8*	5-1/2"	17	New	85001	Comented	700

If changes in the above plans become advisable we will notify you before cementing or landing easing. We estimate that the first productive oil or gas sand should occur at a depth of about 8500 feet.

Additional information:

The Halliburton process will be used on all cementing and cement will be circulated when setting 13-3/8" O.D. Casing.

pproved	
except as follows:	Skelly Oil Company
	By
OIL CONSERVATION COMMISSION,	Send communications regarding well to:
OIL CONSERVATION COMMISSION,	Name Skelly Oil Co.
Pitte Dit & rags Inspect	Address Box 38 - Hobbs, N.M.