

DUPLICATE

(Company or Operator)

County.

..Depth Cleaned Out.

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 6250 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing DEC. 15, 1953
OIL WELL: The production during the first 24 hours was 144.89 barrels of liquid of which 100% was oil; % was emulsion; % water; and % was sediment. A.P.I. Gravity 34 Deg.
GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.
Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico			Northwestern New Mexico		
T. Anhy.	1966'		T. Devonian		T. Ojo Alamo
T. Salt	2064'		T. Silurian		T. Kirtland-Fruitland
B. Salt	2932'		T. Montoya		T. Farmington
T. Yates	3058'		T. Simpson		T. Pictured Cliffs
T. 7 Rivers			T. McKee		T. Menefee
T. Queen			T. Ellenburger		T. Point Lookout
T. Grayburg			T. Gr. Wash		T. Mancos
T. San Andres	4636'		T. Granite		T. Dakota
T. Glorieta	6067'		T.		T. Morrison
T. Drinkard			T.		T. Penn.
T. Tubbs			T.		T.
T. Abo			T.		T.
T. Penn.			T.		T.
T. Miss.			T.		T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	1966	1966	Red Bed				
1966	2932	966	Salt & anhydrite				
2932	3150	218	Anhydrite, lime & sand				
3150	3860	710	Lime & sand				
3860	6250	2390	Lime				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Dec. 21, 1953 (Date)
Company or Operator Skelly Oil Company Address Box 38 - Hobbs, New Mexico
Name Position or Title Dist. Supt.