

# NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELL

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-offs, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

Hobbs, New Mexico

March 25, 1952

Place

Date

OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico.  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

SUNRAY OIL CORPORATION, Maggie Caylor, Well No. 3 in the  
Company or Operator Lease

No. Of Mts. of Sec. 6, T. 17S, R. 37E, N. M. P. M.,  
S. Lovington Field, Lea County

The dates of this work were as follows: March 20, 1952

Notice of intention to do the work was (was not) submitted on Form C-102 on March 19, 1952  
and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

### DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

We set 5 1/2" new casing, 17# & 15.5#, at 8438' Rotary table measurements. Actual pipe in hole 8425.30'. Cemented with 350 sacks, 5% Gel and 60 sacks of Signalite. Top of cement by Temperature Survey is 5712'. Baker Cement Float Collar is one joint off bottom of string. Baker washdown whirler shoe is on bottom of string. Cement was allowed to set for 48 hours and pipe was tested to 1000# for 30 minutes. No drop in pressure was recorded. Drilled out 34' of cement and pipe was again tested to 1000# for 30 minutes. No drop in pressure was recorded.

Witnessed by

Name

Company

Title

Subscribed and sworn to before me this

day of, 19

Notary Public

My Commission expires

I hereby swear or affirm that the information given above is true and correct.

Name

Position Field Supt.

Representing Sunray Oil Corporation  
Company or Operator

Address Box 128, Hobbs, New Mexico

Remarks:

Name

Title

10/10/10