NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in triplicate to the Oil Conservation Commission or its proper agent before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or its agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of notice by checking below:

NOTICE OF INTENTION TO TEST CASING SHUT-OFF	NOTICE OF INTENTION TO SHOOT OR CHEMICALLY TREAT WELL		
NOTICE OF INTENTION TO CHANGE PLANS	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING		
NOTICE OF INTENTION TO REPAIR WELL	NOTICE OF INTENTION TO PLUG WELL	I	
NOTICE OF INTENTION TO DEEPEN WELL			

	Hobbs, New	Mexico	June 25,	1937	
		Place		Date	
OIL CONSERVATION COMMISSION	Ι,				
Santa Fe, New Mexico.					
Gentlemen:					
Following is a notice of intentiton t	o do certain work a	s described below at	the Illinoi	s 011	Company-
Continental	State-Alst		well No. 1	ſn	NE/4
Company or Operator of Sec. 31 , T. 17-S	Lease 37-E	N. M. P. M.,	Horas		Field
Lea	County.		13		

FULL DETAILS OF PROPOSED PLAN OF WORK

Follow INSTRUCTIONS IN THE RULES AND REGULATIONS OF THE COMMISSION This well was drilled to a total depth of 5302' in line 1200' of salt water was encountered at 4745'. 1620' of salt water was encountered at 5208'. A hole full of sulphur water was encountered at 5300'. It is proposed to plug and abandon this well as follows:

A cement plug will be set from **SGR**⁴ the total depth back to 4700⁴. The hole will then be filled with 12 lb. mud from 4700⁴ to 3200⁴ and a cement bridge set from 3200⁴ to 3150⁴. The hole will then be filled with 12 lb. mud from 3150⁴ to the bottom of the 8-5/8⁴ casing cemented at 2020⁴. An attempt will be made to pull the 8-5/8⁴ casing and a cement bridge will be set at the point the pipe is shot off. The hole will be filled with 28 lb. mud from this point back to the base of the 13⁴ surface pipe and a cement bridge set in the bottom of the 15⁴ casing. The hole will then be filled with 12 lb. mud back to a depth of 20⁴ and a cement plug set from 20⁴ back to the surface. The cellar and pits will be filled in and a marker erected according to State regulations.

Approved JUN 28 1937	Illinois Oil Company Pompany or Operator Pro Tell, Cast, II		
	By Tell Sattitt. Position support Send communications regarding well to		
OIL CONSERVATION, COMMISSION,	Name		
By Juy the para	Address		
Title Oil & Cas Inspector			

and the second second second second second



Real and a second

a and a second

and the contract of the second se

and the second production of the