


OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS



Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL		REPORT ON SETTING CASING	X

April 17, 1950

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____
Amerada Petroleum Corporation **Rose Kaves "A"** Well No. **1** in the _____

C/M/4 HZ/4 Company or Operator Lease
of Sec. **2**, T. **17-S**, R. **36-E**, N. M. P. M.,
Exiles Field, **Lee** County.

The dates of this work were as follows: **April 15, 1950**

Notice of intention to do the work was ~~submitted~~ submitted on Form C-102 on **April 15,** 19**50**
and approval of the proposed plan was ~~obtained~~ obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

12,585' - Total Depth - Line - Ran 100 Jts. 5½" O.D. 20#, Grade E, Range 2, S. S. casing, 163 Jts. 5½" O.D. 17#, Grade 8640, Range 3, S. S. Casing & 67 Jts. 5½" O.D. 17#, Grade N-80 Extremeline, Range 3, S. S. Casing - Set at 12556'. 14 Ea. 5½" OD Weatherford Scratchers from 12551' to 12357' & 12 5½" OD Baker Centralizers from 12546' to 12216'. Circulated & worked casing & cemented with 600 sacks Trinity Sls-Sec cement mixed 3% Gel & 1/4# of Flo-Seal per sack. Plug to 12466' at 10:30 P.M., 4-15-50, Maximum Pump Pressure 2200#.

Witnessed by **C. E. Nichols** **Amerada Petroleum Corporation** **Farm Boss**
Name Company Title

Subscribed and sworn before me this
17th day of **April** 19**50**

Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name **Dr. T. J. [Signature]**Position **Assistant District Superintendent**Representing **Amerada Petroleum Corporation**

Company or Operator

My commission expires **10-24-53**Address **Drawer D, Monument, New Mexico**

Remarks:

APPROVED

APR 19 1950

Ray Yorkrough
Name **Ray Yorkrough**
Title

