


DUPLICATE

## OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS



Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

December 3, 1949

Monument, New Mexico

Date

Place

OIL CONSERVATION COMMISSION,  
SANTA FE, NEW MEXICO  
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the \_\_\_\_\_

Amerada Petroleum Corporation Rose Eaves "A" Well No. 1 in the \_\_\_\_\_  
Company or Operator Lease  
C/NW/4 NE/4 of Sec. 2, T. 17-S, R. 38-E, N. M. P. M.,  
Knowles Field, Lee County.

The dates of this work were as follows: December 3, 1949

Notice of intention to do the work was ~~(insert)~~ submitted on Form C-102 on November 30, 1949  
and approval of the proposed plan was ~~(insert)~~ obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

4818' - Total Depth - Anhydrite & Lime. Ran Temperature Survey - Found top of cement 2305' behind 8-5/8" Csg. Actual fill 2513' - Ratio of actual to calculated fill 35.2%. Ran Bit & Found top of cement plug at 4732' - Tested csg. with 1200# for 1/2 hour - satisfactory. Drilled out cement plug and tested csg. with 1200# for 1/2 hour - satisfactory. Started drilling 7-7/8" hole at 4:00 P.M. 12-3-49.

Witnessed by C.E. Nichols Amerada Petroleum Corporation Fern Bos  
Name Company Title

Subscribed and sworn before me this  
3rd day of December 1949

[Signature]  
Notary Public

I hereby swear or affirm that the information given above is true and correct.

Name [Signature]

Position Assistant District Superintendent

Representing Amerada Petroleum Corporation  
Company or Operator

My commission expires 10-24-53

Address Drawer D, Monument, New Mexico

Remarks:

APPROVED

Date Dec 14 1949

[Signature]  
Name  
Oil & Gas Inspector  
Title