## NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELLS

3:

Submit this leport in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should a specified as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

	Indicate Nature of Report by Checking B	elow
REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON REPAIRING WELL
REPORT ON RESULT DE PLUGGING WELL	REPORT ON RECOMPLETION OPERATION	REPORT ON (Other)
	November 9, 1955	Midland, Taxas
Following is a report on the work	done and the results obtained under the heading	noted above at the
	en Petroleum Comp.	
A.W. Thonyson, Icc.	, Well No	in the 112 1/4 Hr 1/4 of Sec. 2
	th Knowles Devonder Pool,	
	November 3, 1955	
DETAIL  DF111ed 17-1/4" hole	(was not) submitted on Form C-102 on	1ed on C-101 LTS OBTAINED 13-3/8" 48# H-40 R2
Drilled 17-1/4" hole  8TC New Gasing 280.5"	(MARGINET) obtained. Approval outain LED ACCOUNT OF WORK DONE AND RESULT to 300' K.B. Set 9 jts of 7'. Set at 296.27' K.B. & Liburton. Plug down @ 12:3' ag w/1000 psi clear water provided to the second prov	13-3/8" 48# H-40 R2 Cemented w/350 sx Longhor P.M. on 11-2-55. Circula
Drilled 17-1/4" hole  STC New Gasing 280.5'  common coment by Hall  coment. Tested casin  hour. No Pressure	(MARGINE) obtained. Approval obtainment of work done and result to 300' K.B. Set 9 jts of 7'. Set at 296.27' K.B. & Liburton. Plug down @ 12:3' ag w/1000 psi clear water princes.	13-3/8" 48# H-40 R2 Cemented w/350 sx Longhor P.M. on 11-2-55. Circula
Drilled 17-1/4" hole STC New Gasing 280.5"  semmon cement by Hali	(MARGINET) obtained. Approval outain LED ACCOUNT OF WORK DONE AND RESULT to 300' K.B. Set 9 jts of 7'. Set at 296.27' K.B. & Liburton. Plug down @ 12:3' ag w/1000 psi clear water provided to the second prov	13-3/8" 48# H-40 R2 Cemented w/350 sx Longhor P.M. on 11-2-55. Circula
Drilled 17-1/4" hole  STC New Casing 280.5'  common coment by Hall  coment. Tested easing 1 hour. No Pressure	to 300' K.B. Set 9 jts of  To 300' K.B. Set 9 jts of  The set at 296.27' K.B. &  Liburton. Plug down & 12:3'	13-3/8" 48# H-40 R2 Cemented w/350 ex Longhor P.M. on 11-2-55. Circula ressure in 24 hours for  Tarm Boss (Title)