


OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS



Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	<input checked="" type="checkbox"/>		

Artesia, New Mexico

October 4, 1945

Place

Date

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

E. J. McGurdy Jr. State "A" Well No. 1 in the
Company or Operator Lease
SE/4 of SE/4 of Sec. 16, T. 18 S, R. 32E, N. M. P. M.,
Wildcat Field, ROCKY Lea County.

The dates of this work were as follows: September 5, 1945 intermittently to October 1, 1945

Notice of intention to do the work was (~~was not~~) submitted on Form C-102 on September 5, 1945
and approval of the proposed plan was (~~was not~~) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Plugged back with tamped lime rock from 4676' to 4650' and cemented with 5 sks.; filled with mud to approximately 4600'; attempted to pull the 7" pipe - would not start, pumped loose by Halliburton; recovered 4613' of 7"; bridge with tamped lime rock from 4350' to 4325', and cemented with 5 sks.; mudded to approximately 2475'; bridge from 2475' to 2450' with tamped lime rock; cement with 5 sks.; filled with mud to 1200'; bridge with tamped lime rock 1200' to 1180'; cement with 5 sks.; knocked off 8-5/8" casing at 775'; mudded to 775'; bridged with lime rock and cemented with 5 sacks; mudded to 750'; bridged with lime rock; cemented with 10 sks.; bailed for 12 hours to clean up hole.

Witnessed by R. E. Roark Name E. J. McGurdy Jr. Supt.
Company Title

Subscribed and sworn before me this

I hereby swear or affirm that the information given above is true and correct.

4 day of October, 1945Name R. E. RoarkMildred HudsonPosition Production Supt.

Notary Public

Representing E. J. McGurdy Jr.
Company or OperatorMy commission expires 4/3/48Address 807 Fair Building, Fort Worth, Texas

Remarks:

Row Yourboat
Name
Title