



(SUBMIT IN TRIPLICATE)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYLand Office New MexicoLasso No. 09245

Unit \_\_\_\_\_

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	
NOTICE OF INTENTION TO PULL OR ALTER CASING		SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

July 23, 19 57

Well No. 2 is located 990 ft. from N line and 2310 ft. from W line of sec. SW/4, Sec. 20  
(1/4 Sec. and Sec. No.) (18 S. (32 E. NMPM  
(Twp.) (Range) (Meridian)  
Young Lea New Mexico  
(Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 3761 ft. DF, 3750 GL

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

We propose to drill to a total depth of approximately 4050 ft; set 1025 ft. of 8 5/8 - 28 lb. casing with 200 sx. of posmix; set 4050 ft.-J-55-5 1/2"-14.5 lb. casing with 150 sx. posmix; perforate either the Upper of Middle Queen with dyna-jet, 4 shots per ft; wash with 250 gallons of mud acid and fracture with 10,000 gallons of oil and 15,000 lbs. of sand.

COPIED  
JUL 2 1957

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company John M. Beard  
Address 1300 North Broadway  
Oklahoma City  
Oklahoma  
By F. H. Hartman  
Title F. H. Hartman  
Geologist