



(SUBMIT IN TRIPLICATE)

 UNITED STATES
 DEPARTMENT OF THE INTERIOR
 GEOLOGICAL SURVEY

 Budget Bureau No. 42-R358.4.
 Approval expires 12-31-60.
Land Office Santa Fe, N.M.Lease No. 88-01707Unit I

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL		SUBSEQUENT REPORT OF WATER SHUT-OFF	
NOTICE OF INTENTION TO CHANGE PLANS		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF		SUBSEQUENT REPORT OF ALTERING CASING	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE		SUBSEQUENT REPORT OF ABANDONMENT	<input checked="" type="checkbox"/>
NOTICE OF INTENTION TO PULL OR ALTER CASING	<input checked="" type="checkbox"/>	SUPPLEMENTARY WELL HISTORY	
NOTICE OF INTENTION TO ABANDON WELL			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

Maybelle Miller

8/23/67, 19 67

Well No. 1 is located 1980 ft. from S line and 495 ft. from E line of sec. 22

NE/4 SE/4 22 19-S 33-E RM
 (1/4 Sec. and Sec. No.) (Twp.) (Range) (Meridian)

Tonto Los New Mexico
 (Field) (County or Subdivision) (State or Territory)

The elevation of the derrick floor above sea level is 3634 ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

On 7/10/67 the depleted productive zone, 3400-3445, in this well was plugged with 135 sacks of cement with 325 lbs of Gilsomite, mixed 13 lbs to the sack in the first 25 sacks. Cement was squeezed to 1000 lbs PSI without pressure loss. The hole was circulated with Aquagel mud. This work done by Halliburton.

On July 24th, the Artesia Casing pullers moved on location to salvage casing and finish plugging well. Cement in 7" Casing found to be at 2800' (Base of Sale 2940). After several attempts down hole, the 7" Casing was finally shot off at 1248 feet in 8-5/8" cased hole and pulled. A cement plug of 20 sacks was placed at top of 7" casing stub (1248-1348'). The 8-5/8" casing was recovered from a depth of 705' with a 20 sack cement plug being placed in the top of the 8-5/8" casing stub from 700'. A 20 sack cement plug was used at surface and regulation marker erected. Location cleaned for final abandonment. This work completed 8/19/67

APPROVED

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company T.J. Sivley & Mondo Drilling Company

DEC 28 1967

Address P.O. Drawer 00J L GORDON
ACTING DISTRICT ENGINEERArtesia, New Mexico 88210By [Signature]
Title Owner-Operator