



(SUBMIT IN TRIPLICATE)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Budget Bureau No. 42-R358.4.
Approval expires 12-31-60.

Land Office **Santa Fe, N.M.**

Lease No. **NM-01707**

Unit **1**

(Comm. Agr. 57 Tonto shallow
Gas Unit, NM-01707, NM-02796
and NM-030941)

SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	SUBSEQUENT REPORT OF WATER SHUT-OFF.....
NOTICE OF INTENTION TO CHANGE PLANS.....	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....	SUBSEQUENT REPORT OF ALTERING CASING.....
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....	SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....	SUBSEQUENT REPORT OF ABANDONMENT.....
NOTICE OF INTENTION TO PULL OR ALTER CASING.....	SUPPLEMENTARY WELL HISTORY.....
NOTICE OF INTENTION TO ABANDON WELL.....	

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

June 29, 1966, 19 **66**

Waybelle Miller

Well No. **1** is located **1980** ft. from **N** line and **495** ft. from **E** line of sec. **22**

NE/4SE/4 22 (1/4 Sec. and Sec. No.) **19-8** (Twp.) **33-4** (Range) **NMPM** (Meridian)
Tonto (Field) **Lee** (County or Subdivision) **New Mexico** (State or Territory)

The elevation of the derrick floor above sea level is **3634** ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Permission is requested to plug and abandon this well. Production has declined far below the economic limit, and further remedial efforts to improve does not exist. Final production ceased in April 1966, and the well has been shut in since that date. Plugging proposal is made to circulate hole with mud, fill 7" casing with cement back to 2900 feet, (base of salt 2940') thus shutting off all productive zone open, 3400-3441. Recover as much 7" casing as possible above 2900', then set 20 sack cement plug at 1700' for top of salt protection (1715'). Attempt will then be made to recover as much 8-5/8" casing set @ 1452' with 30 sacks of cement as possible. If recovery is below 900', a 20 sack plug will be set @ 900 feet in possible Santa Rosa water zone, otherwise 20 sack plug will be placed at shot off point of 8-5/8" casing. When the above has been accomplished, a 20 sack plug will be placed at surface and regulation marker erected, and location cleaned up for final abandonment.

Set plug at 1400'-1500' instead of 1700'

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Company **T.J. Sivley & Son's Drilling Company**

Address **P.O. Drawer 60**

Artesia, New Mexico

APPROVED
As Amended
JUL 1 1966
R. L. BROWN
DISTRICT ENGINEER

By **T.J. Sivley**
Owner-Operator

Title