

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBS OFFICE OCC

MISCELLANEOUS REPORTS ON WELLS

JUN 29 PM 1:14

Submit this report in **TRIPLICATE** to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL	X	REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

June 24, 1954

(Date)

P.O. Box 1638, Midland, Texas

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

L. F. Oil Company

(Company or Operator)

Auraria State

(Lease)

McQueen & Stunt Drilling Company

(Contractor)

Well No. 1 in the SE 1/4 SW 1/4 of Sec. 23

T. 17 S., R. 34 E., NMPM, Vacuum Pool, Lea County.

The Dates of this work were as follows: June 12, 13, 1954

Notice of intention to do the work (was) (~~none~~) submitted on Form C-102 on June 8, 1954, 19, (Cross out incorrect words)

and approval of the proposed plan (was) (~~none~~) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

T.D. 4978'. The 5 1/8" casing is cemented at 4935'; Used Halliburton and put in 35 sacks of cement between 4930' and 4978' (T.D.); then filled hole with mud mixed by Halliburton inside the 5 1/8" casing, from 4930' back to surface; then shot-off the 5 1/8" casing at 781' and pulled 781' of 5 1/8" casing. Set cement plug (10 sacks) from 781' to 715'; Set cement plug at 680' (the bottom of the 3 5/8" surface casing is at 680'); the plug is from 680' to 540'; and from 540' to surface; used five sacks of cement for plug at surface. Then set a pipe, 4" in diameter, in concrete; this 4" pipe rises four feet above the surface.

Witnessed by F. Arthur Stunt
& Bob Freyher (tool pusher)

McQueen & Stunt Drilling Company,

(Company)

Partner

(Title)

Approved:

OIL CONSERVATION COMMISSION

H. A. Johnson
(Name)

District Inspector

(Title)

(Date)

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name

W. Dave Henderson

Position

Geologist

Representing L. F. Oil Company

Address 1208 Commerce Bldg., Houston 2, Texas

