

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State ☒ Fee ☐
5. State Oil & Gas Lease No. B2317

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT TO DRILL" (FORM C-101) FOR SUCH PROPOSALS.)	
1. OIL WELL ☐ GAS WELL ☐ OTHER ☐	7. Unit Agreement Name --
2. Name of Operator Phillips Petroleum Company	8. Farm or Lease Name M. E. Hale
3. Address of Operator Room 806, Phillips Bldg., Odessa, Tx 79761	9. Well No. #4
4. Location of Well UNIT LETTER N 660 FEET FROM THE South LINE AND 1980 FEET FROM THE West LINE, SECTION 35 TOWNSHIP 17-S RANGE 34-E N.M.P.M.	10. Field and Pool, or Wildcat Vacuum (Gb/San Andres)
11. Elevation (Show whether DF, RT, GR, etc.) 4029 RKB	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐	COMMENCE DRILLING OPNS. ☐
PULL OR ALTER CASING ☐	CASING TEST AND CEMENT JOB ☐
OTHER ☐	OTHER ☐
PLUG AND ABANDON ☐	ALTERING CASING ☐
CHANGE PLANS ☐	PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

(1-20) RU Ralph Johnson Unit, pld rods & tbgs. Ran 2-3/8" tbgs w/Model R pkr w/spotting valve set 4575'. Spt 300 gals BJ 1 step gyp solvent #2 dn tbgs followed w/13.3 BW, 4.6 BW to sqz in form thru perfs 4622-4650'. Press vac. SI 18 hrs.

(1-21) Open spotting valve, swbd 6 hrs from 4300', 23 BLW. Sqz in 1 drum Baroid WT 344, 1 drum 814 mixed w/20 BW. Overflsh w/120 BW, mixed w/5 gal S-32. Pmpd in on vac. SI 16 hrs.

(1-22) SD 24 hrs.

(1-23) Pmpg. COOH w/tbgs & tools. Set 2-3/8" tbgs open end @ 4650', ran rods & 2" X 1 1/2" X 12' pmp set 4649'. MO Ralph Johnson WS. Pmpd 16 hrs, no gauge.

(1-24) Pmpd 24 hrs, 31 BO, 55 BLW, 12-44" SPM w/1 1/2" pmp.

(1-25) Pmpd 24 hrs, 77 BO, 36 BLW.

(1-26) Pmpd 24 hrs, 66 BO, 15 BLW.

(1-27) Pmpd 24 hrs, 95 BO, 15 BW, GOR 1129/1, perfs 4622-51'. Restored to production.

Series 900 POP, 3000% WP, w/one set fluid rams, one set pipe rams, manually operated.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W. J. Mueller TITLE Engineering Advisor DATE 1-30-78

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: