	-1088 <b>5</b>	Budget Bureau No. 42–R358.4. Approval expires 12–31–60.	
Form 9-331a (Feb. 1951)	(SUBMIT IN TRIPLICATE) UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	Land Office Lease No. Unit	NM 086 NM 086 MAR 2 4 1959 MAR 2 4 1959 MAR 3 64 10 0001 00 000 MAR 3 64 10 0000 0000 MAR 3 64 10 0000 0000 MAR 3 64 10 00000 MAR 3 64 10 0000 MAR 3 64 10000 MAR 3 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7

COPY TO O. C. C.

## SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL. NOTICE OF INTENTION TO CHANGE PLANS NOTICE OF INTENTION TO TEST WATER SHUT-OFF NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL NOTICE OF INTENTION TO SHOOT OR ACIDIZE NOTICE OF INTENTION TO PULL OR ALTER CASING NOTICE OF INTENTION TO ABANDON WELL	SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING				
(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)					
	March 23,	, 1959			
Well No. 3 is located 1980t. from $\begin{cases} N \\ S \end{cases}$ line and 1980 ft. from $\begin{cases} E \\ W \end{cases}$ line of sec. 25					
NE/4, SW/4, Sec. 25 (% Sec. and Sec. No.) Unassigned	34-E NMPM   (Range) (Meridian)   Lea New Mex   County or Subdivision) (State or Territory)	ico			

The elevation of the derrick floor above sea level is 3742 ft.

## DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

Well is to be drilled to the Queen Sand at approximately 5100'. Surface casing will consist of 8-5/8"  $\bigcirc$ . D. 24# casing set at approximately 300' and cemented to surface. Production casing will be 4-1/2"  $\bigcirc$ . D. 9. 50# casing set at total depth and cemented with sufficient cement for protection through the salt section.

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.		
Company	Cabot Carbon Company	
Address	<u>Box 4395, Midland, T</u> exas	
		By
		Title Dist. Prod. Supt.
		GP0 862040