

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	5a. Indicate Type of Lease State ☒ Fee ☐
2. Name of Operator Phillips Petroleum Company	5. State Oil & Gas Lease No. B 1497
3. Address of Operator Room 711, Phillips Bldg., Odessa, Texas 79761	7. Unit Agreement Name Vacuum Abo Unit
4. Location of Well UNIT LETTER G 2080 FEET FROM THE north LINE AND 1980 FEET FROM THE east LINE, SECTION 26 TOWNSHIP 17-S RANGE 35-E NMPM.	8. Farm or Lease Name Btry Vacuum Abo Unit Tract
	9. Well No. 70 6E
	10. Field and Pool, or With-out Vacuum Abo Reef
	12. County Lea
15. Elevation (Show whether DF, RT, GR, etc.) 3926' RKB	

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☒
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐
OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1-21-76: MI Well Units rig. Pld tbg & pkr.
1-22-76: Plugged back from 8720' to 8653' w/2 sx sand and 600# Hydromite
1-23-76: Ram guns perf 5 1/2" csg w/4" csg gun w/2 shots per foot 8578-83'. Set 2-3/8" tbg at 8500' w/Baker R pkr on bottom. Runco treated down tbg through perfs 8578-8648' w/2500 gals 28% NE HCL acid w/one ball sealer per bbl. Flushed w/40 BW. Max press 2800#, min 1600#, ISDP 0# AIR 5.2 BPM. Swbd 3 hrs, 40 BLW. SI 14 hrs, TP 500#.
1-24-76: F/24 hrs, 28/64" ch, 300 BO, 15 BAW, FTP 250#
1-25-76: F/24 hrs, 28/64" ch, 314 BO, 14 BAW, FTP 250#
1-26-76: F/24 hrs, 28/64" ch, 320 BO, 8 BAW, GOR 1625/1, FTP 250#, perfs 8578-8648'.
Restored to production.

BOP Eqpt: Series 900, 3000# WP, double, with one set blind rams, one set pipe rams

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W. J. Mueller BY Engineering Advisor

DATE 1-27-76

APPROVED BY Supv. TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: