

NEW MEXICO OIL CONSERVATION COMMISSION  
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER) SANDFRAC	X	NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO

Roswell, New Mexico  
(Place)

November 7, 1960  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Shell Oil Company State N Well No. 3 in G  
(Company or Operator)  
SW NE 1/4 of Sec. 28, T. 17S, R. 35E, NMPM, Vacuum Pool  
(40-acre Subdivision)  
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK

(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

1. Pull tubing, run Caliper Survey of open hole.
2. Run 3" X-line frac tubing w/Lynes formation packer set at approximately 4425'.
3. Treat below packer w/15,000 gallons lease oil containing 1# sand/gallon & sufficient FLA to maintain spurt loss less than 10 cc & 30-minute fluid loss less than 20 cc.
4. Leave shut in one hour. Bleed off pressure, pull 3" tubing & packer, plug back open hole w/sand to 4425'. Rerun 3" tubing w/packer set immediately below casing shoe if packer seat available. If no seat available, set packer in casing.
5. Treat w/15,000 gallons lease oil containing 1# sand/gallon.
6. Shut in overnight, bleed off pressure and pull 3" tubing.
7. Clean out sand to TD.
8. Run tubing, swab test, place on pump.
9. Recover load and place on production.

Approved....., 19.....  
Except as follows:

Approved  
OIL CONSERVATION COMMISSION

By.....

Title.....

Shell Oil Company

Company or Operator

Original Signed By  
By..... R. A. Lowery..... R. A. LOWERY

Position..... District Exploitation Engineer  
Send Communications regarding well to:

Shell Oil Company

Name.....

Address..... Box 845, Roswell, New Mexico