NEW MEAICO OIL CONSERVATION COMMISSICAL Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELL

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-offs, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nat	ture of report by checking	g below:	
REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON RE	PAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL	REPORT ON P	ULLING OR OTHERWISE CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	REPORT ON DI	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	•		
Hobi	os. New Mexico	January 23.	1950
OIL CONSERVATION COMMISSION, Santa Fe, New Mexico.	Place	Date	
Gentlemen: Following is a report on the work done and the	e results obtained under the	DUPLICA besiding noted above at the	
Shell Petroleum Corporation		Well No.	in the
COMPANY OR OPERATOR	LEASE	11/20	n the
	39, T178	, R, N.2	M., M.,
		IAA 4/1/2	_ Control
The dates of this work were as follows:		C-102 ont incorrect words) ESULTS OBTAINED	-/9 ₃₉ -////
	WORK DONE AND R		-Q.
Cemented hole from 4310 to 463 and pulled same. Mudded hole of 8 5/8 inch casing with 40 s	t Limestone. 5	inch casing set and ded hole with head inch casing at 30 Set cement plug in the casing at 30 set cemen	at 4350 avy mud. 000 feet in bottom
Cemented hole from 4310 to 463 and pulled same. Mudded hole of 8 5/8 inch casing with 40 s 5/8 inch casing with 15 sack	t Limestone. 5	inch casing set and ded hole with head inch casing at 30 Set cement plug in the casing at 30 set cemen	at 4350 avy mud. 000 feet in bottom
Cemented hole from 4310 to 463 and pulled same. Mudded hole of 8 5/8 inch casing with 40 s 5/8 inch casing with 15 sack	t Limestone. 5	inch casing set and ded hole with head inch casing at 30 Set cement plug in the casing at 30 set cemen	at 4350 Evy mud. OOO feet In bottom In top onest Repor
Cemented hole from 4310 to 463 and pulled same. Mudded hole of 8 5/8 inch casing with 40 s 5/8 inch casing with 15 sack Witnessed by Name	t Limestone. 5. t 1653 feet. Mo 57 feet. Shot 5. with heavy mud. acks. Remudded s. Well plugged	inch casing set and added hole with head inch casing at 30 Set cement plug in hole and set plug and abandoned. Later affirm that the information etc.	at 4350 avy mud. 000 feet in bottom in top on the Repor
Cemented hole from 4310 to 463 and pulled same. Mudded hole of 8 5/8 inch casing with 40 s 5/8 inch casing with 15 sack Witnessed by Name	t Limestone. 5 t 1653 feet. M 7 feet. Shot 5 with heavy mud. acks. Remudded s. Well plugged Company I hereby swear of is true and correct Name	inch casing set and ded hole with head inch casing at 30 Set cement plug in hole and set plug and abandoned. Later affirm that the information	at 4350 avy mud. 000 feet in bottom in top on the Repor
Cemented hole from 4310 to 463 and pulled same. Mudded hole of 8 5/8 inch casing with 40 s 3 5/8 inch casing with 15 sack Witnessed by	t Limestone. 5 It 1653 feet. M If feet. Shot 5 With heavy mud. Backs. Remudded Sompany I hereby swear of is true and correct Name	inch casing set and added hole with head inch casing at 30 Set cement plug in hole and set plug and abandoned. Later affirm that the information etc.	at 4350 avy mud. 000 feet in bottom in top onest Repor
Cemented hole from 4310 to 463 and pulled same. Mudded hole of 8 5/8 inch casing with 40 s 3 5/8 inch casing with 15 sack Witnessed by	t Limestone. 5. It 1653 feet. Management of the street of	inch casing set and ded hole with head inch casing at 30 Set cement plug is hole and set plug and abandoned. Later affirm that the information of the control of the contro	at 4350 avy mud. 000 feet in bottom in top on the porton given above
Cemented hole from 4310 to 463 and pulled same. Mudded hole of 8 5/8 inch casing with 40 s 3 5/8 inch casing with 15 sack Witnessed by	t Limestone. 5. It 1653 feet. Management of the street of	inch casing set and ded hole with head inch casing at 30 Set cement plug is hole and set plug and abandoned. La Title or affirm that the information ct. La Company or Ope Company or Ope Company or Ope	at 4350 avy mud. 000 feet in bottom in top of the portion given above

\$ 14

NEW ME CONTROL OF STANDARD CONTRACTOR OF STAN

MISCHELARROUS ARROATS ON VOICE

The large of the large of the policy make the superior of the policy field of the large of the l