

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.
30-025-08539

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
B-1400-3

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator
Phillips Petroleum Company

3. Address of Operator
4001 Penbrook Street, Odessa, TX 79762

4. Well Location
Unit Letter O : 990 Feet From The South Line and 1980 Feet From The East Line
Section 33 Township 17S Range 35E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)
3940' GL; 3945' RKB

7. Lease Name or Unit Agreement Name

East Vacuum Gb/SA Unit
Tract 3315

8. Well No.
003

9. Pool name or Wildcat
Vacuum Gb/SA

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. MIRU DDU. NU Class II BOP.
2. GIH and set 4-1/2" CICR at 4145' w/2-3/8" N-80 workstring.
3. Squeeze with Plug No. 1 (75 sx cement) in open hole 4145'-4635'. Cap CICR with 20 sx cement. This will cover the San Andres and Grayburg. Circ. 4-1/2" csg. with 9.5 ppg mud-laden fluid.
4. Spot Plug No. 2 (20 sx cement) 2788'-2888'. This will cover the Yates.
5. Perforate the 4-1/2" csg. at 1625'. Set pkr. at 1475'. Squeeze with Plug No. 3 (50 sx. cement) 1500'-1625'. This will cover the salt section and the 7-5/8" casing shoe. Tag plug.
6. Perforate and circulate with Plug No. 4 (70 sx cement) 3'-340' leaving the 4-1/2" casing and the 7-5/8" x 4-1/2" annulus full of cement. This will cover the water table and surface plug.
7. Cut off casing 3' below ground level. Install monument marker. Perform reclamation work.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE L. M. Sanders TITLE Supv. Regulatory Affairs DATE 04-29-94

TYPE OR PRINT NAME L. M. Sanders

TELEPHONE NO. 368-1488

(This space for State Use)

APPROVED BY _____

CONDITIONS OF APPROVAL, IF ANY:

ORIGINAL SIGNED BY JERRY SEATON
DISTRICT SUPERVISOR

THE COMMISSION HAS BEGINNING
YOUR PRIOR TO THE BEGINNING
RECORDING OF THE LAND
DATE APPROVED

DATE MAY 03 1994

RECEIVED

MAY 22 1984

JOHN HUBBS
ADMIN