NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

NUMBER OF COPI	ES RECEIVED		_
	TRIBUTION		
SANTA FE		T	
FILE			
U. B. G . 9.			
LAND OFFICE			
TRANSPORTER	OIL		
	GAS		
PRORATION OFFI	CE		
00554700			

WELL RECORD

		1,50	<u> </u>			
			83	Or:	·• ,	
493	20	134				
	_		ੳ	Ρ/,	, - 3	
						7
	198	19.20	19.22 May	500 575	1832 May 8	18.2 An. 18.5

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE

If State Land submit 6 Copies

AREA 640 ACRES
LOCATE WELL, CORRECTLY Santa Fe Phillips Petroleum Company (Company or Operator) (Lease) 26 175 35E NW SW 67 ..., NMPM.¼ of... ..¼, of Sec. Well No. Undesignated 660 west south 1882 5-31-62 4-4-62 Drilling Commenced... Phillips Petroleum Company Rig No. 30 Name of Drilling Contractor... Bartlesville, Oklahoma Address..... Not confidential 19 OIL SANDS OR ZONES 9033¹ (TD) No. 4, from......to..... 8475 to... _____to______ No. 6, from..... IMPORTANT WATER SANDS Include data on rate of water inflow and elevation to which water rose in hole.feet. No. 2, from..... CASING BECORD KIND OF SHOE CUT AND PULLED FROM WEIGHT PER FOOT NEW OR PERFORATIONS PURPOSE SIZE AMOUNT 3-3/8" 8-5/8" Surface 48# New 3201 Baker 32591 Baker Intermediate 24 New -1/2^H 90161 Hallib. 8512 - 88561 Production 17-20# New MUDDING AND CEMENTING RECORD NO. SACKS METHOD WHERE SET MUD GRAVITY AMOUNT OF MUD USED SIZE OF SIZE OF 17-1/4 13-3/8 3351 350 Pump-plug 400 32751 12-1/4 8-5/8 90331 Ħ 7-7/8" 5-1/2 520 RECORD OF PRODUCTION AND STIMULATION (Record the Process used, No. of Qts. or Gals. used, interval treated or shot.) Acidized with 1000 gallons 15% regular acid Result of Production Stimulation Flowed 24 hours - 815 barrels oil, no water.

Depth Cleaned Cut.....

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary	tools w	ere used from	surface	feet (. TD (9033') feet,	and from		feet to	fcet.
Cable t	oou we	re used from		teet 1	to	feet,	and from		feet to	feet.
						UCTION				
			e 7, 1962		-					
OIL W	ELL:									9.7 % was
						-	% wat	er; and	%	was sediment. A.P.I.
		Gravity	9.0	•••••	•••••••••••••••••••••••••••••••••••••••					
GAS W	ELL:	The producti	on during the first	24 ho	urs was		M.C.F.	plus		barrels of
			carbon. Shut in Pre				·	•		01
Length	of Tim	e Shut in			***************************************	,				
PL	EASE	INDICATE 1	BELOW_FORMAT	TION	TOPS (IN CON	FORMAN	ICE WIT	н сеосі	RAPHICAL SECTI	ON OF STATES.
			Southeastern 1	lew M					Northwestern	
T. Ani	hy Ru	stler	1643	Ť.	Devonian		• • • • • • • • • • • • • • • • • • • •	Т.		
					Silurian					
B. Salt	t	•	2660	T.	Montoya	••••••••		т.		
			2580		Simpson					•
			3742	T.	McKee					
T. Gra	en vhura		4043	Т. Т.	Ellenburger					
			4320	T.	Gr. Wash					
			6060	Т.						
T. Rei	electi ^C	learfork	6170	T.						
				T.	***************************************			т.		
			8475	T.		· · · · · · · · · · · · · · · · · · ·			•	
				Т.			·•••••	т.		•••••
I. Miss	S	•••••••••••••••••••••••••••••••••••••••	······································	T.	FORMATIO			т.		
From	То	Thickness	For	matio			1	Thickness		
0	1460	In reet	Redbed		11	From	То	in Feet	Form	nation
1460 2093 4560 8490 8965	209; 4566 8496 896; 903; TI	633 2467 3930 475 68	Redbed, anh Anhydrite, Lime Lime, dolom Dolomite	salt	.t• 					
alu C	- 103	3 filed 3	4-92 te Ce abo Rey top	hre-	c‡					
			ATTACH SEPA	TR A T	E SHEET IF A	DDITTO	JAT SD:	CE to the		

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

	Video Op A 7000	
Company or Operator. Phillips Petroleum Company	Address Bex 2105 - Hobbs,	New Mexico
	Position or Title District Chief	