

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE	X	NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	X	NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICOHobbs, New Mexico
(Place)December 22, 1964
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Socony Mobil Oil Company, Inc. State "NM" Well No. 12 in.....
(Company or Operator) (Unit)
NW 1/4 NW 34 T. 17S R. 35E NMPM, Vacuum Abo Reef Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

TD 9100' - PBTD 9023

7 5/8" Csg. @ 3600' w/1650 sx. 6% gel. 5 1/2" liner set from 3452' to 9100' w/720 sx.
Perf. 8491-8914'

Propose to test present perfs. open new perfs. from 8927, 8935 & 8959 and acidize new perfs.
Kill well with crude oil and pull rods & tubing. Run Baker retrievematic packer to 8450'.
Swab well until stabilized. Keep swab report (oil, water & gas volumes & fluid level).
Reset packer at 8770' and swab unit stabilized. Keep swab report. Perforate thru tubing
at 8927, 8935 and 8959 with 3/8" jetshots. Use Western Gammatron log (dated 1-16-63)
to correlate. Reset packer at 8920'. Set packer rubber at 8920. Spot gelled acid to
by-pass valve on packer. Pump away at 8 BPM, 2500 gallons acid + 3 ball sealers. Pull
tubing and packer and complete.

Approved..... December 22, 1964
Except as follows:Approved
OIL CONSERVATION COMMISSIONBy.....
Title.....

Socony Mobil Oil Company, Inc.
By.....
Position..... Group Supervisor
Send Communications regarding well to:

Name..... Socony Mobil Oil Company, Inc.
Address..... Box 1800, Hobbs, New Mexico