

COUNTY	I		FIELD Undesignated		STATE N.M.		NO
OPR	Cactus Drilling Company						MAP
NO.	2 LSE Pure-State						
SEC.	36	T	19S	R	34E	SUR	CO-ORD
LOC.	1980' fr S Line & 660' fr E Line of Sec.						
MI.	FROM		CLASS.		EL. 37132		
SPUD.	5-31-63	COMP.	6-19-63	FORMATION	DATUM	FORMATION	DATUM
IRT.	250 Ac.	SOF	30,000	LOG:			
	+ 90,000# sd.			Anhy	1830		
CSG. & SX.				Yates	3420		
	8 5/8"	104'	75	Queen	4600		
	4 1/2"	5023'	200	Penr	4928		
TBG.	DEPTH	SIZE					
LOGS	EL	GR	RA	IND	HC	A	
				TD	5026'	PB	4994'
PROD INT.	(DAILY RATE)	BS&W	GH	GOR	GTY	C. P.	T. P.
4882-90'	Swab 45 BO				35.		24'
(Queen)							
Distribution limited and publication prohibited by subscribers' agreement. Reproduction rights reserved by Williams & Lee Scouting Service, Inc.							
CONT.	Co. Tools			PROP DEPTH 5100'		TYPE	
DATE							

F.R. 5-31-63, Queen test. PD 5100', - Co. Tools

6-4-63 Drlg. 3570' anhy.

6-11-63 Drlg. 4821'.
Cored 4770-4820', rec 50' being: 2' dolo., 6' sd., NS, & 42' dolo.

6-18-63 TD 5026', recovering load.
Cored 4885-4938', rec 53' being: 3' dolo., 15' sd., w/6' show, 30' dolo., 5' sh., w/show.
Cored 4938-91', rec 53' being: 18' sd., w/4' show, 35' dolo.
Cored 4991-5026', rec 35' being: 9' sd., NS, 5' dolo., 10' sd., NS, 11' dolo., NS.
Perf 32/4882-90', treated 250 gals acid,
SOF 30,000 gals + 90,000# sd.

6-24-63 TD 5026', PB 4994', ppg. load.

7-1-63 TD 5026', PB 4994', COMPLETED.