

COUNTY <u>Lea</u>		FIELD <u>Scharb-Bone Springs</u>		STATE <u>N.M.</u>		NO. <u> </u>	
OPR <u>Cactus Drilling Company</u>				MAP <u> </u>			
NO. <u>1</u>		LSE <u>Hooper, Guy H. et al "B"</u>					
EC. <u>7</u>	T. <u>19S</u>	BLK <u>35E</u>	SUR. <u> </u>	CO-ORD. <u> </u>			
LOC. <u>660' fr N & E Lines of Sec.</u>							
MI. <u> </u>		FROM <u> </u>		CLASS <u> </u>		EL. <u>3895</u>	
SPUD. <u>8-8-63</u>		COMP. <u>9-8-63</u>		FORMATION <u> </u>		DATUM <u> </u>	
RT. <u>A</u>		4500 gals		LOG:			
				Anhy 1842			
CSG. & SX.				Yates 3558			
13 3/8" 421' 400				Queen 4595			
8 5/8" 3992' 400				SA 5200			
4 1/2" 10250' 300				B Spgs 7835			
TBG. DEPTH		SIZE		B Spgs Poro			
LOGS EL GR RA IND HC A				10108			
				TD 10250		PB 10225'	
PROD INT.		(DAILY RATE)		BS&W GH GOR		STY C. P. T. P. HRS. TEST	
10111-131'		Flo. 480 BO		16/64"		38. 500# 1025# 24	
(Bone Springs)							
Distribution limited and publication prohibited by subscribers' agreement. Reproduction rights reserved by Williams & Lee Scouting Service, Inc.							
CONT. Co. Tools				PROP. DEPTH 10,500' TYPE			
DATE							

8-8-63,
PD 10,500' RT - Bone Springs
Contractor - Company Tools

8-13-63 Drlg. 3840'.
8-20-63 Drlg. 6030'.
8-27-63 Drlg. 8920'.
9-4-63 TD 10250', prep to run casing.
DST 10103-126', open 2 hrs, used 2000' WB
GTS 6 mins, OTS 75 mins
Fld. est. 10 bbls oil to pits in 45 mins,
Rev out Full String of oil,
60 min ISIP 4189#, FP 1254-3250#
120 min FSIP 4189#.

9-10-63 TD 10250', tstg.
Perf (Bone Springs) 10111-131' W/4 JSPF
Ac 500 gals
Flwd 10-15 BNOPH thru 16/64" choke

9-16-63 TD 10250', PB 10225', COMPLETED.
Re-A 4000 gals