

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
B2146	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL <input checked="" type="checkbox"/> WELL GAS <input type="checkbox"/> WELL OTHER- <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Amerada Hess Corporation	8. Farm or Lease Name State V "B"
3. Address of Operator Drawer D, Monument, New Mexico 88265	9. Well No. 2
4. Location of Well UNIT LETTER <u>K</u> <u>2310</u> FEET FROM THE <u>South</u> LINE AND <u>2310</u> FEET FROM THE <u>West</u> LINE, SECTION <u>36</u> TOWNSHIP <u>17S</u> RANGE <u>34E</u> N.M.P.M.	10. Field and Pool, or Wildcat Vacuum Glorieta
15. Elevation (Show whether DF, RT, GR, etc.) 4009' DF	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input checked="" type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

2-2-84 to 2-10-84 - Pulled rods, pump & tbq. Selectively perf. 5-1/2" csg. opposite Glorieta zone fr. 5978' to 5992' & fr. 5997' to 6003'. Ran pkr. & tbq., set pkr. at 5838'. Acidized Glorieta zone thru 5-1/2" csg. perf. fr. 5930' to 6012' w/2000 gal. 15% NE acid using ball sealers as diverter. Swabbed load. Pulled tbq. & pkr. Ran 3-1/2" drlg. bailer & drld. bridge plug at 6100' & pushed bridge plug to 6250'. Perf. 5-1/2" csg. opposite Glorieta zone selectively fr. 6067' to 6149'. Ran pkr. & tbq. & set pkr. at 6029'. Acidized Glorieta zone thru 5-1/2" csg. perf. fr. 6067' to 6149' w/3000 gal. 15% NE acid using ball sealers as diverter. Swabbed load. Pulled tbq. & pkr. Re-ran tbq., pump & rods. Changed out 114 pump unit for 160 pump unit and resumed pumping 5-10-84.

Test of 2-12-84: Pumped 74 b.o. & no water in 24 hrs. on 10-74" SPM.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.		
SIGNED <u>EA Fisher</u>	TITLE <u>Supv. Adm. Ser.</u>	DATE <u>2-13-84</u>
ORIGINAL SIGNED BY JERRY SEXTON		
APPROVED BY <u>DISTRICT SUPERVISOR</u>	TITLE <u></u>	DATE <u>FEB 15 1984</u>
CONDITIONS OF APPROVAL, IF ANY:		

RECEIVED

FEB 14 1984

O.C.D.
ADDRESS OFFICE