to Appropriate District Office	Ene, Minerals and Natural 1	féxico Resources Department	Form C-103 Revised 1-1-89
<u>DISTRICT I</u> P.O. Box 1980, Hobbs, NM 88240	OIL CONSERVATIO		WELL API NO.
DISTRICT II P.O. Drawer DD, Artesia, NM 88210	Santa Fe, New Mexico	87504-2088	5 Indicate Type of Lease
DISTRICT III			5. Indicate Type of Lease STATE FEE X
1000 Rio Brazos Rd., Aztec, NM 87410			6. State Oil & Gas Lease No.
(DO NOT USE THIS FORM FOR PROF DIFFERENT RESERV	CES AND REPORTS ON WE POSALS TO DRILL OR TO DEEPE YOIR. USE "APPLICATION FOR PI 101) FOR SUCH PROPOSALS.)	N OR PLUG BACK TO A	7. Lease Name or Unit Agreement Name
1. Type of Well: ONL GAS WELL XX WELL	OTHER		Ora Jackson "A"
2. Name of Operator			8. Well No.
Big "6" Drilling Compan	У		2
Address of Operator			9. Pool name or Wildcat
<u>c/o Oil Reports & Gas S</u> 4. Well Location	ervices, Inc., Box 75	5. Hobbs,NM	Wildcat Oueen
Unit Letter :660	Feet From The North	Line and 19	80 Feet From The West Lin
Section 8	Township 19S R 10. Elevation (Show whether	Ange 35E	NMPM Lea County
	//////	• DF, KKB, KI, GR, etc.) • 3 GR	
1. Check A	ppropriate Box to Indicate	Nature of Notice R	enort or Other Data
NOTICE OF INTE	ENTION TO:		SEQUENT REPORT OF:
		REMEDIAL WORK	ALTERING CASING
	CHANGE PLANS	COMMENCE DRILLING	
JLL OR ALTER CASING		CASING TEST AND CE	
		CASING TEST AND CE	
THER:		OTHER:	[
THER: 2. Describe Proposed or Completed Operation		OTHER:	· · · · · · · · · · · · · · · · · · ·
2. Describe Proposed or Completed Operation work) SEE RULE 1103.	os (Clearly state all pertinent details, a	OTHER:	ling estimated date of starting any proposed
THER: 2. Describe Proposed or Completed Operation work) SEE RULE 1103. Perf Queen 4656-66 with	os (Clearly state all pertinent details, a 2 shots per foot. Rat	OTHER:	ling estimated date of starting any proposed
THER: 2. Describe Proposed or Completed Operation work) SEE RULE 1103. Perf Queen 4656-66 with It is proposed to plug a	os (Clearly state all periment details, a 2 shots per foot. Ran as follows:	OTHER:	ling estimated date of starting any proposed Pump 100% water.
THER: 2. Describe Proposed or Completed Operation work) SEE RULE 1103. Perf Queen 4656-66 with It is proposed to plug a Set cast iron bridge plu Cut & pull 4 1/2" casing	us (Clearly state all periment details, a 2 shots per foot. Ran as follows: 1g at 4500 & cap with 1g from 4000'. Spot cer	OTHER: ad give pertiment dates, includ in tubing & rods. 20' cement, Loan ment plug 3950 t	ding estimated date of starting any proposed Pump 100% water.
THER: 2 Describe Proposed or Completed Operation work) SEE RULE 1103. Perf Queen 4656-66 with It is proposed to plug a Set cast iron bridge plu Cut & pull 4 1/2" casing 4 1/4" casing stub at 40	2 shots per foot. Ran as follows: ag at 4500 & cap with g from 4000'. Spot cer 2000' & 8 5/8" casing s	OTHER: ad give pertiment dates, include in tubing & rods. 20' cement, Loan ment plug 3950 to shoe at 3989.	ding estimated date of starting any proposed Pump 100% water. d hole with mud. o 4050 to cover
THER: 2 Describe Proposed or Completed Operation work) SEE RULE 1103. Perf Queen 4656-66 with It is proposed to plug a Set cast iron bridge plu Cut & pull 4 1/2" casing 4 1/4" casing stub at 40 Cut & pull 8 5/8" casing	cs (Clearly state all perimens details, a 2 shots per foot. Ran as follows: 1g at 4500 & cap with 1g from 4000'. Spot cer 1000' & 8 5/8" casing s 1g from 1500'. Spot cer	OTHER: and give pertiment dates, include in tubing & rods. 20' cement, Loan ment plug 3950 to shoe at 3989. ment plug 1450 to	ding estimated date of starting any proposed Pump 100% water. d hole with mud. o 4050 to cover
THER: 2 Describe Proposed or Completed Operation work) SEE RULE 1103. Perf Queen 4656-66 with It is proposed to plug a Set cast iron bridge plu Cut & pull 4 1/2" casing 4 1/4" casing stub at 40 Cut & pull 8 5/8" casing Spot 100' cement plug ac	as (Clearly state all perimens details, a 2 shots per foot. Ran as follows: 1g at 4500 & cap with g from 4000'. Spot cer 2000' & 8 5/8" casing s g from 1500'. Spot cer cross 13 3/8" casing s	OTHER: of give periment dates, include in tubing & rods. 20' cement, Loan ment plug 3950 to shoe at 3989. ment plug 1450 to shoe at 402'.	ting estimated date of starting any proposed Pump 100% water. d hole with mud. o 4050 to cover o 1550.
THER: 2 Describe Proposed or Completed Operation work) SEE RULE 1103. Perf Queen 4656-66 with It is proposed to plug a Set cast iron bridge plu Cut & pull 4 1/2" casing 4 1/4" casing stub at 40 Cut & pull 8 5/8" casing	as (Clearly state all perimens details, a 2 shots per foot. Ran as follows: 1g at 4500 & cap with g from 4000'. Spot cer 2000' & 8 5/8" casing s g from 1500'. Spot cer cross 13 3/8" casing s	OTHER: of give periment dates, include in tubing & rods. 20' cement, Loan ment plug 3950 to shoe at 3989. ment plug 1450 to shoe at 402'.	ting estimated date of starting any proposed Pump 100% water. d hole with mud. o 4050 to cover o 1550.
THER: 2 Describe Proposed or Completed Operation work) SEE RULE 1103. Perf Queen 4656-66 with It is proposed to plug a Set cast iron bridge plu Cut & pull 4 1/2" casing 4 1/4" casing stub at 40 Cut & pull 8 5/8" casing Spot 100' cement plug ac	as (Clearly state all perimens details, a 2 shots per foot. Ran as follows: 1g at 4500 & cap with g from 4000'. Spot cer 2000' & 8 5/8" casing s g from 1500'. Spot cer cross 13 3/8" casing s	OTHER: of give periment dates, include in tubing & rods. 20' cement, Loan ment plug 3950 to shoe at 3989. ment plug 1450 to shoe at 402'.	ting estimated date of starting any proposed Pump 100% water. d hole with mud. o 4050 to cover o 1550.
THER: 2 Describe Proposed or Completed Operation work) SEE RULE 1103. Perf Queen 4656-66 with It is proposed to plug a Set cast iron bridge plu Cut & pull 4 1/2" casing 4 1/4" casing stub at 40 Cut & pull 8 5/8" casing Spot 100' cement plug ac	as (Clearly state all perimens details, a 2 shots per foot. Ran as follows: 1g at 4500 & cap with g from 4000'. Spot cer 2000' & 8 5/8" casing s g from 1500'. Spot cer cross 13 3/8" casing s	OTHER: of give periment dates, include in tubing & rods. 20' cement, Loan ment plug 3950 to shoe at 3989. ment plug 1450 to shoe at 402'.	ting estimated date of starting any proposed Pump 100% water. d hole with mud. o 4050 to cover o 1550.
THER: 2 Describe Proposed or Completed Operation work) SEE RULE 1103. Perf Queen 4656-66 with It is proposed to plug a Set cast iron bridge plu Cut & pull 4 1/2" casing 4 1/4" casing stub at 40 Cut & pull 8 5/8" casing Spot 100' cement plug ac	as (Clearly state all perimens details, a 2 shots per foot. Ran as follows: 1g at 4500 & cap with g from 4000'. Spot cer 2000' & 8 5/8" casing s g from 1500'. Spot cer cross 13 3/8" casing s	OTHER: of give periment dates, include in tubing & rods. 20' cement, Loan ment plug 3950 to shoe at 3989. ment plug 1450 to shoe at 402'.	ting estimated date of starting any proposed Pump 100% water. d hole with mud. o 4050 to cover o 1550.
THER: 2 Describe Proposed or Completed Operation work) SEE RULE 1103. Perf Queen 4656-66 with It is proposed to plug a Set cast iron bridge plu Cut & pull 4 1/2" casing 4 1/4" casing stub at 40 Cut & pull 8 5/8" casing Spot 100' cement plug ac Spot 10 sack plug at sur	as (Clearly state all perimens details, a 2 shots per foot. Ran as follows: 1g at 4500 & cap with g from 4000'. Spot cer 2000' & 8 5/8" casing s g from 1500'. Spot cer 2005 13 3/8" casing s cface with regulation	OTHER: ad give pertinent dates, include in tubing & rods. 20' cement, Loan ment plug 3950 to shoe at 3989. ment plug 1450 to shoe at 402'. marker. Clean &	ting estimated date of starting any proposed Pump 100% water. d hole with mud. o 4050 to cover o 1550.
THER: 2 Describe Proposed or Completed Operation work) SEE RULE 1103. Perf Queen 4656-66 with It is proposed to plug a Set cast iron bridge plu Cut & pull 4 1/2" casing 4 1/4" casing stub at 40 Cut & pull 8 5/8" casing Spot 100' cement plug ac Spot 10 sack plug at sur	as (Clearly state all periment details, a 2 shots per foot. Ran as follows: 1g at 4500 & cap with g from 4000'. Spot cer 200' & 8 5/8" casing s g from 1500'. Spot cer cross 13 3/8" casing s cface with regulation	OTHER: nd give pertiment dates, includ a tubing & rods. 20' cement, Loan ment plug 3950 to shoe at 3989. ment plug 1450 to shoe at 402'. marker. Clean &	ting estimated date of starting any proposed Pump 100% water. d hole with mud. o 4050 to cover o 1550.
THER: 2 Describe Proposed or Completed Operation work) SEE RULE 1103. Perf Queen 4656-66 with It is proposed to plug a Set cast iron bridge plu Cut & pull 4 1/2" casing 4 1/4" casing stub at 40 Cut & pull 8 5/8" casing Spot 100' cement plug ac Spot 10 sack plug at sur hereby certify that the information above is true and	as (Clearly state all perimens details, a 2 shots per foot. Ran as follows: 1g at 4500 & cap with g from 4000'. Spot cer 2000' & 8 5/8" casing s g from 1500'. Spot cer 2005 13 3/8" casing s cface with regulation	OTHER: nd give pertiment dates, includ a tubing & rods. 20' cement, Loan ment plug 3950 to shoe at 3989. ment plug 1450 to shoe at 402'. marker. Clean &	ting estimated date of starting any proposed Pump 100% water. d hole with mud. o 4050 to cover o 1550.
THER: 2 Describe Proposed or Completed Operation work) SEE RULE 1103. Perf Queen 4656-66 with It is proposed to plug a Set cast iron bridge plu Cut & pull 4 1/2" casing 4 1/4" casing stub at 40 Cut & pull 8 5/8" casing Spot 100' cement plug ac Spot 10 sack plug at sur hereby certify that the information above is true and NONATURE Memory.	as (Clearly state all periment details, a 2 shots per foot. Ran as follows: 1g at 4500 & cap with g from 4000'. Spot cer 200' & 8 5/8" casing s g from 1500'. Spot cer cross 13 3/8" casing s cface with regulation	OTHER: nd give pertiment dates, includ a tubing & rods. 20' cement, Loan ment plug 3950 to shoe at 3989. ment plug 1450 to shoe at 402'. marker. Clean &	Ting estimated date of starting any proposed Pump 100% water. d hole with mud. o 4050 to cover o 1550. level location.
Perf Queen 4656-66 with It is proposed to plug a Set cast iron bridge plu Cut & pull 4 1/2" casing 4 1/4" casing stub at 40 Cut & pull 8 5/8" casing Spot 100' cement plug ac Spot 10 sack plug at sur hereby certify that the information above is true and HONATURE MOMME	as (Clearly state all periment details, a 2 shots per foot. Ran as follows: 1g at 4500 & cap with g from 4000'. Spot cer 200' & 8 5/8" casing s g from 1500'. Spot cer cross 13 3/8" casing s cface with regulation d complete to the best of my knowledge and 2 mm	OTHER: nd give pertiment dates, includ a tubing & rods. 20' cement, Loan ment plug 3950 to shoe at 3989. ment plug 1450 to shoe at 402'. marker. Clean &	<pre>ding estimated date of starting any proposed Pump 100% water. d hole with mud. o 4050 to cover o 1550. level location. DATE5-1-89</pre>
THER: 2 Describe Proposed or Completed Operation work) SEE RULE 1103. Perf Queen 4656-66 with It is proposed to plug a Set cast iron bridge plu Cut & pull 4 1/2" casing 4 1/4" casing stub at 40 Cut & pull 8 5/8" casing Spot 100' cement plug ac Spot 10 sack plug at sur hereby certify that the information above is true and KONATURE Memory Additional Store Complete This space for State Use) OperCINAL SIGNE	as (Clearly state all pertinent details, a 2 shots per foot. Ran as follows: 1g at 4500 & cap with g from 4000'. Spot cer 200' & 8 5/8" casing s g from 1500'. Spot cer cross 13 3/8" casing s cface with regulation d complete to the best of my knowledge and 2 mm	OTHER: nd give pertiment dates, includ a tubing & rods. 20' cement, Loan ment plug 3950 to shoe at 3989. ment plug 1450 to shoe at 402'. marker. Clean &	<pre>ding estimated date of starting any proposed Pump 100% water. d hole with mud. o 4050 to cover o 1550. level location. DATE</pre>
THER: 12 Describe Proposed or Completed Operation work) SEE RULE 1103. Perf Queen 4656-66 with It is proposed to plug a Set cast iron bridge plu Cut & pull 4 1/2" casing 4 1/4" casing stub at 40 Cut & pull 8 5/8" casing Spot 100' cement plug ac Spot 100' cement plug ac Spot 10 sack plug at sur hereby certify that the information above is true and HONATURE	as (Clearly state all periment details, a 2 shots per foot. Ran as follows: 1g at 4500 & cap with g from 4000'. Spot cer 200' & 8 5/8" casing s g from 1500'. Spot cer cross 13 3/8" casing s cface with regulation d complete to the best of my knowledge and 2 mm	OTHER: ad give pertiment dates, include a tubing & rods. 20' cement, Load ment plug 3950 to shoe at 3989. ment plug 1450 to shoe at 402'. marker. Clean & belief. the Agent	<pre>ding estimated date of starting any proposed Pump 100% water. d hole with mud. o 4050 to cover o 1550. level location. DATE5-1-89</pre>
THER: 2 Describe Proposed or Completed Operation work) SEE RULE 1103. Perf Queen 4656-66 with It is proposed to plug as Set cast iron bridge plu Cut & pull 4 1/2" casing 4 1/4" casing stub at 40 Cut & pull 8 5/8" casing Spot 100' cement plug ac Spot 10 sack plug at sur hereby certify that the information above is true and HONATURE Mem.t. Holds: This space for State Use) ORIGINAL SIGNE	as (Clearly state all periment details, a 2 shots per foot. Ran as follows: 1g at 4500 & cap with g from 4000'. Spot cer 200' & 8 5/8" casing s g from 1500'. Spot cer cross 13 3/8" casing s cface with regulation d complete to the best of my knowledge and 2 mm ED BY JERRY SEXTON 1 SUPERVISOR	OTHER: nd give pertinent dates, include In tubing & rods. 20' cement, Loan ment plug 3950 to shoe at 3989. ment plug 1450 to shoe at 402'. marker. Clean & belief. LEAgent	<pre>ding estimated date of starting any proposed Pump 100% water. d hole with mud. o 4050 to cover o 1550. level location. level location. DATE</pre>
THER: 2. Describe Proposed or Completed Operation work) SEE RULE 1103. Perf Queen 4656-66 with It is proposed to plug as Set cast iron bridge plu Cut & pull 4 1/2" casing 4 1/4" casing stub at 40 Cut & pull 8 5/8" casing Spot 100' cement plug ac Spot 10 sack plug at sur hereby certify that the information above is true and KNATURE Memory of State Use) YPE OR PRINT NAME This space for State Use) ORIGINAL SIGNE DISTRICT PEROVED BY	as (Clearly state all periment details, a 2 shots per foot. Ran as follows: 1g at 4500 & cap with g from 4000'. Spot cer 200' & 8 5/8" casing s g from 1500'. Spot cer cross 13 3/8" casing s cface with regulation d complete to the best of my knowledge and 2 mm ED BY JERRY SEXTON 1 SUPERVISOR	OTHER: ad give pertinent dates, include In tubing & rods. 20' cement, Loan ment plug 3950 to shoe at 3989. ment plug 1450 to shoe at 402'. marker. Clean & belief. LEAgent	ting estimated date of starting any proposed Pump 100% water. d hole with mud. o 4050 to cover o 1550. level location. DATE

•

MAY 2 1989 OCD MOBBS OFFICE

1. j (* 150