12/1/63

SUMMARY OF OPERATIONS

10/6/63	Commenced drilling operation @ 12:10 a.m. (spud date).
10/9/63	Set 1520' of 9-5/8" surface casing.
10/9/63	Ran temperature survey.
10/10/63	Tested 9-5/8" casing w/800# for 30 mins.
10/23/63	Fished and recovered 10 drill collars, stabilizer and bit in 153 hrs.
11/12/63	PGAC ran Acoustic-GR log 100-6842.
11/12/63	PGAC ran Laterolog 2900-6837.
11/12/63	Worth Well ran Caliper Survey 1500-6840'.
11/13/63	Set 6850' of 7" production casing.
11/14/63	Worth Well ran Temperature Survey 0-6789'.
11/14/63	Released Gardner Bros. drilling rig @ 11:00 a.m.
11/18/63	Rig up Lohmann Well Service derrick unit.
11/18/63	Drilled out cement 6781-6830.
11/19/63	Tested 7" casing w/1500# for 30 mins.
11/19/63	Squeezed outside of 7" casing w/250 sx. cement.
11/19/63	Worth Well ran GR Collar Log 5800-6834.
11/19/63	Worth Well perf. 7" casing 6569-6807 w/l JSPF.
11/20/63	Dowell, Inc. acidized perfs. 6569-6807 w/1000 gal. 15% NE acid.
11/21/63	Pulled tbg. & pkr.
11/21/63	Western Co. sand oil frac perfs. 6569-6807 down 7" csg. w/15000 gal. refined oil + 30,000# 20-40 Ottawa sand + 1/20#/gal. Adomite M-2 in 3 stages using 28 RCN ball sealers.
11/22/63	Ran 2" tbg. & set @ 6547'.
11/29/63	Pulled 2" tbg. & pkr.
11/29/63	Set Baker Model D pkr. w/knockout plug @ 6548'. Set ret. bridge plug @ 6075'.
11/29/63	Frontier perf. 7" casing 5916-5932 and 5940-5960.
11/29/63	Ran 2" tbg. & pkr., set @ 5898'.
11/30/63	BJ Service acidized perfs. 5916-5932 & 5940-5960 w/1000 gal. 15% NE acid.
12/1/63	Recovered bridge plug @ 6075'.
10/11/00	a a face

Ran 2-3/8" Blinebry tbg. to 6552', latched in pkr. @ 6548'. Seating nipple @ 6542'. Ran 2-3/8" Glorieta tbg. to 5959', tbg. perfs. @ 5927. seating nipple @ 5926'. Installed ROP