

COUNTY	LEA	FIELD	Scharb	STATE	N.M.
OPR	HUMBLE OIL & REFG. COMPANY				MAP
1 Adkins, Eugene B. et al					
Sec. 5, T-19-S, R-35-E					
660' fr S Line & 1980' Fr E Line of Sec.					
Spudded 12-27-63					
P&A 2-6-64		CLASS		EL 3868'	
		FORMATION	DATUM	FORMATION	DATUM
CSG & SX - TUBING		LOG:			
13 3/8" 428' 475		Yates 3358			
8 5/8" 3983' 500		Queen 4624			
		Penr 4913			
		SA 5186			
		Del Mt 6060			
LOGS EL GR RA IND HC A		B Spg 7688			
		TD 10,179'			

PLUGGED & ABANDONED

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT.	PROP DEPTH 10,300'	TYPE
DATE		

F.R. 12-26-63; Oper's Elev. 3868'. Df
PD 10,300' - Bone Springs

12-30-63 Drlg. 1520'.
1-6-64 TD 3983', prep to drill.
1-13-64 Drlg. 5943'
1-20-64 Drlg. 8197' lm.
1-27-64 Drlg. 9610'.
2-3-64 TD 10,179', pulling test tool.
Cored 10,087-137', rec 28' shly dolo., w/tr.
bldg. oil 10087-088'.
Cored 10,137-154', rec 17' shly dolo., w/NS.
Cored 10,154-179', rec 25' shly dolo., w/NS.
DST 10,104-179', mis-run.

2-10-64 TD 10,179', PLUGGED & ABANDONED.
DST 10,104-179', open 1 hr,
Used 1500' WB, Rec WB + 5' mud,
1 hr ISIP 934#, FP 758-758#,
2 hr FSIP 851#.
Side Wall Cored @ 10,104', 10,106', 10,

-conti.

