

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-7

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

0+6 - NMOCD - P.O. Box 1980 1 - Foreman EF
Hobbs, NM 88240
1 - Engr. Lee Martin 1 - File
1-Mr. J.A. -Midland, 1-Laura Richardson-Midland

5a. Indicate Type of Lease
State ☒ For ☐
5. State Oil & Gas Lease No.
B-1565

SUNDARY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT - 1" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL <input checked="" type="checkbox"/> GAS <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Getty Oil Company	8. Farm or Lease Name State BA
3. Address of Operator P.O. Box 730 Hobbs, NM 88240	9. Well No. 7
4. Location of Well UNIT LETTER C 660 FEET FROM THE N LINE AND 1880 FEET FROM THE W LINE, SECTION 36 TOWNSHIP 17S RANGE 34E NMPM.	10. Field and Pool, or Wildcat Vac: Glor. & Blinebry
15. Elevation (Show whether DF, RT, GR, etc.) 4010' DF	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

Abandon Blinebry. Add perfs and acidize Glorieta

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

This well is a slim-hole dual completion, with the west string perforated in the Glorieta and the east string perforated in the Blinebry. We propose to abandon the Blinebry zone, additionally perforate and stimulate in the Glorieta, and commingle the two strings in the Glorieta to allow for a "vent" string.

1. Pull rods, pump from Glorieta string.
 2. TIH w/2 7/8" pkr. on 1" tbg. string to 5900' in Glorieta string and test for csg. leaks. Squeeze if necessary.
 3. Similarly test Blinebry string for csg. leaks to 6200'. Squeeze if necessary.
 4. Set 2 7/8" CIBP at 6200' in Glorieta string.
 5. Dump sand across Glorieta perfs, and pressure string to 1000#.
 6. Via Blinebry string, squeeze Blinebry perfs with 75 sxs. cement. Displace cmt. to 6200'.
 7. Test to 1000# to insure Blinebry perfs are plugged. If not, set 2 7/8" CIBP on top of cement.
 8. Clean sand out of Glorieta string.
 9. Perforate Glorieta in west string (oriented away from east string) at 5903, 04, 10, 12, 13, 32, 33, 34, 44, 45, 78, 79, 97, 6000, 01, 04, 05, 06, 09, 11, 13, 17, 24, 26, 34,
- (Continued on back)

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Dale R. Crockett TITLE Area Superintendent DATE October 14, 1983

ORIGINAL SIGNED BY JERRY SEXTON

APPROVED BY DISTRICT SUPERVISOR

CONDITIONS OF APPROVAL, IF ANY:

OCT 24 1983

- 41, 42, 66, 67, 74, 75, 78, 86, 87, 88, (total of 35 holes). Perforate 10 shots at 6110' with a spiral gun (3-4 shots will hit east string).
10. Acidize Glorieta with 5000 gal. 15% HCl.
 11. Swab well.
 12. Run rods and pump in east string. West string will be used to flow gas.

RECEIVED

OCT 20 1988

O.C.D.
MOBBS OFFICE