STATE OF NEW MEXICO "O" NCT-1 NO. 12

13 UL 10 M 10 16

Spudded 11" hole 5:00 A.M. December 14, 1962.

Ran 1588' of 8-5/8" OD casing and cemented at 1599'. Cement with 480 sacks of Incor 8% Gel and 100 sacks of Grade "A" cement. Cement circulated. Job complete 7:00 P.M. December 15, 1962. Tested 8-5/8" O.D. casing with 600 psi from 5:00 P.M. to 5:30 P.M. December 16, 1962. Tested OK. Drilled plug and retested with 600 psi from 7:30 P.M. to 8:00 P.M. December 16, 1962. Tested OK. Job complete 8:00 P.M. December 16, 1962.

Ran Electric Log on January 8, 1962.

Ran Strings "Y" (Glorieta) and "Z" (Blinebry): Cement both strings with 500 sacks of 1:1 Pozmix and Incor, 2% Gel. Pump plugs down with 200 gals acetic acid in each string. Tested both strings with 2000 psi for 30 minutes. Tested OK. Job complete 3:15 A.M. January 6, 1963.

Undesignated (Blinebry): San 8908' of 2-7/8" O.D. casing and cemented at 6919'. Plug at t866'. Ferforate 2-7/8" O.D. casing with 1 jet shot per foot 6558-6569', 6591-6617'. Acidize with 1000 gals of LSTNEA in 4 stages with 3 ball scalers. Squeezed perforations at 6558', 6569', 6591' and 6617' with 100 sacks of Incor Neat cement. Perforate at 6388', 6407', 6420', 6434', 6457', 6468' with 1 jet shot per interval. Acidize perforations with 2000 gals of 15% LSTNEA in 7 stages, 285 gals/stage with 6 ball scalers between stages. Frac with 15,000 gals of refined oil. Squeeze casing perforations with 150 sacks of Class "C" cement with LW additive. Displace cement to 6288'. Complete 11 A.M. February 14, 1953. Drill out cement from 6169' to 6347'. Drilled cement from 6347' to 6430'. Circulate hole. Perforate 2-7/8" casing with 1 jet shot per interval 6350', 6369', 6388', 6407', 6420'. Acidize with 500 gallons acetic acid. Abandon Held For Possible Future Development, July 5, 1963.

Undesignated (Glorieta): Ran 6906' of 2-7/8" casing and cemented at 6918'. Plug at 6887'. Perforate 2-7/8" O.D. casing with 1 jet shot per foot from 5945-5949'. Acidize with 1000 gallons of 15% LSTNEA. On 24 hour potential test well flowed thru 19/64" choke 240 BO and no water ending 8:00 A.M. January 11, 1963.

Gravity 35.8

GOR 908

Top of Pay 5945'

Bottom of Pay 5949'

TEXACO Inc. Date 1-11-63

NMOCC Date 1-5-63