

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State ☐	Fee ☒
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL ☒ WELL GAS ☐ WELL OTHER ☐	7. Unit Agreement Name
2. Name of Operator EXXON CORPORATION	8. Farm or Lease Name CHARLES S. ALVES
3. Address of Operator P.O. Box 1600, MIDLAND, TEXAS 79701	9. Well No. 1
4. Location of Well UNIT LETTER B 660 FEET FROM THE NORTH LINE AND 1980 FEET FROM THE EAST LINE, SECTION 7 TOWNSHIP 19-S RANGE 35-E NMPM.	10. Field and Pool, or Wildcat SCHARR-BONE SPRINGS
15. Elevation (Show whether DF, RT, GR, etc.) 3910 RDB	12. County LEA

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☒
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOB ☐	OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

11-19-74, MIRU BABER WELL SERV., PLD 2 3/8" TBC, RAN HALLIBURTON 8 5/8 RETAINER, SET @ 2500, TESTED TBC TO 1200 #, HELD OK, PMPD WTR BELOW RETAINER, CIRC ABOVE RETAINER, INDICATED HOLE IN 8 5/8 CSC ABOVE RETAINER, SPOTTED 35' CMT PLUG ABOVE RETAINER, PLD TBC. 11-20-74, WELDED PULL NIPPLE ON 8 5/8 CSC, INDICATED TO BE STUCK @ 700', PERFD 8 5/8 CSC @ 1800'. 11-21-74, RAN 2 3/8 TBC IN HOLE TO 1798, SPOT 75 SK CMT PLUG, PLD TBC OUT, PMPD 5 BBLs WTR, PRESS INCR TO 1600 #, PMPD IN 11 BBLs INTO FORMATION @ 1200 # @ 2 BPM, 60 SK CMT INTO FORMATION, AFTER 15 MIN SIP 600 #. 11-22-74, CUT 8 5/8 CSC AT 705, PLD & LAID DN 24 JTS CSC, RAN 2" TBC TO 747'. 11-23-74, SPOT 100 SK CMT PLUG @ 747 TO 600, PLD TBC UP TO 445, SPOT 100 SK CMT PLG @ 445-300, PLD TBC, SPOT 20 SK CMT PLUG @ SURFACE, SET DRY HOLE MARKER. FRW 11-23-74

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Nathan E. Clegg TITLE SECTION HEAD DATE 12-10-74

APPROVED BY Nathan E. Clegg TITLE SECTION HEAD DATE 12-10-74
CONDITIONS OF APPROVAL, IF ANY: