



IN REPLY REFER TO:

UNITED STATES
DEPARTMENT OF THE INTERIOR

GEOLOGICAL SURVEY
P. O. Drawer 1857
Roswell, New Mexico 88201

RECEIVED O.C.C.
JAN 30 3 40 PM '64

January 29, 1964

William A. & Edward R. Hudson
302 Carper Building
Artesia, New Mexico

Gentlemen:

Your Notice of Intention to Drill well No. 6 Signal Ross (copy attached) in the SW $\frac{1}{4}$ SE $\frac{1}{4}$ sec. 30, T. 19 S., R. 33 E., N.M.P.M., Lea County, New Mexico, lease New Mexico 073240, to a depth of 3,500 feet to test the Yates-Seven Rivers formation, has been forwarded to this office for approval.

Pursuant to authority delegated to the Regional Oil and Gas Supervisor on May 10, 1962, 27 F.R. 4814, I hereby approve the Notice of Intention to Drill described in the foregoing.

Please notify the District Engineer, Geological Survey, P. O. Box 1157, Hobbs, New Mexico, in sufficient time for a representative to witness all cementing operations.

Sincerely yours,

(ORIG. Sgd.) JOHN A. ANDERSON

JOHN A. ANDERSON
Regional Oil and Gas Supervisor


Attachment
cc:

Washington
Mining Branch (2)
NMOCG-Hobbs (2) (w/2 cys Notice)✓
Hobbs
Roswell(2)

(SUBMIT IN TRIPLICATE)

Land Office New MexicoUNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYLease No. 078240Unit 9

JAN 30 3 40 PM '64



SUNDRY NOTICES AND REPORTS ON WELLS

NOTICE OF INTENTION TO DRILL.....	<input checked="" type="checkbox"/>	SUBSEQUENT REPORT OF WATER SHUT-OFF.....	
NOTICE OF INTENTION TO CHANGE PLANS.....		SUBSEQUENT REPORT OF SHOOTING OR ACIDIZING.....	
NOTICE OF INTENTION TO TEST WATER SHUT-OFF.....		SUBSEQUENT REPORT OF ALTERING CASING.....	
NOTICE OF INTENTION TO RE-DRILL OR REPAIR WELL.....		SUBSEQUENT REPORT OF RE-DRILLING OR REPAIR.....	
NOTICE OF INTENTION TO SHOOT OR ACIDIZE.....		SUBSEQUENT REPORT OF ABANDONMENT.....	
NOTICE OF INTENTION TO PULL OR ALTER CASING.....		SUPPLEMENTARY WELL HISTORY.....	
NOTICE OF INTENTION TO ABANDON WELL.....			

(INDICATE ABOVE BY CHECK MARK NATURE OF REPORT, NOTICE, OR OTHER DATA)

January 24, 1964

Signal Rock
Well No. #6 is located 660 ft. from S line and 1980 ft. from E line of sec. 30SW 1/4 SE 1/4 Sec. 30
(1/4 Sec. and Sec. No.)198
(Twp.)33E
(Range)T11N
(Meridian)Wilcox
(Field)Lee
(County or Subdivision)New Mexico
(State or Territory)

The elevation of the derrick floor above sea level is _____ ft.

DETAILS OF WORK

(State names of and expected depths to objective sands; show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work)

It is proposed to drill a Yates-John Rivers test with cable tools to a depth of approximately 3300'. Approximately 75' of 13-3/8" casing will be cemented to the surface. Approximately 600' of 10-3/4" and 1000' of 8-3/8" casing will be run as cave strings and will be pulled. We will cement 5 1/2" casing through the pay with 150 sacks of 4 1/2 gal regular cement plus 100 sacks of neat regular. Completion will be made by perforating 5 1/2" and treating.

Circulate mud behind oil string

I understand that this plan of work must receive approval in writing by the Geological Survey before operations may be commenced.

Perry E. Mann - Little Rock Unit

Company William A. & Edward F. Rudson, AgentAddress 302 Carper BuildingArtesia, New Mexico

By

*Ralph L. Gray*Title Consulting Engineer.