

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instruction:
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 052

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐	7. UNIT AGREEMENT NAME Mescalero Ridge
2. NAME OF OPERATOR ERNEST A. HANSON	8. FARM OR LEASE NAME Mescalero Ridge Unit
3. ADDRESS OF OPERATOR P. O. Box 1515, Roswell, New Mexico	9. WELL NO. 3-35
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FWL & 660' FEL Sec. 35, T. 19 S., R. 34 E., N.M.P.M. Lea County, New Mexico	10. FIELD AND POOL, OR WILDCAT Pearl Queen
14. PERMIT NO.	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 35-19S-34E
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3723' KB	12. COUNTY OR PARISH Lea
	13. STATE New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐FRACTURE TREATMENT ☒SHOOTING OR ACIDIZING ☒(Other) **Running production casing** ☒REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5-1/2", 15-1/2", J-55 casing was set @ 5228' & cemented w/350 sx. incore cement. Top of cement came to 3200 ft. Temp. Survey was run by Coleman Engr. Co., Hobbs, New Mexico.

All reservoir intervals were perforated with 1 - 0.41" jet per foot. Each interval, as designated, was treated limited entry between HOWCO HM straddle packers.

4569-4575'	500 gals. acid, 19,320 gals. lease oil & 17,500 lbs. sand.
4603-4609'	500 gals. acid, 20,000 gals. lease oil & 18,500 lbs. sand.
4713-15, 4837-40'	500 gals. acid, 13,826 gals. lease oil & 9,500 lbs. sand.
4934-39, 4945-46'	1000 gals. acid, 16,926 gals. lease oil & 11,500 lbs. sand.
5077-5083'	1000 gals. acid.

18. I hereby certify that the foregoing is true and correct

SIGNED *Harry L. Schram* TITLE Geologist DATE 3-23-64

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.