Form 3160-5 (June 1990)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

BUREAU OF LAND MANAGEMENT 5. Lease Designation and Serial No. NM-007465-B 652-SUNDRY NOTICES AND REPORTS ON WELLS 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE 891007465B 1. Type of Well Mescalero Ridge Unit Oil Well X Other WIW. 8. Well Name and No. 2. Name of Operator Mescalero Ridge Unit 35 #6 Hondo Oil & Gas Company 9. API Well No. 3. Address and Telephone No. 300252069300S1 P. O. Box 2208, Roswell, NM 88202 (505)625-6732 10. Field and Pool, or Exploratory Area 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Pearl Queen Timb C 11. County or Parish, State 660' FNL & 1980' FWL; Sec.35-T19S-R34E Lea Co., NM CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA 12 TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Change of Plans Recompletion New Construction Subsequent Report Plugging Back Non-Routine Fracturing Casing Repair Water Shut-Off Final Abandonment Notice Altering Casing Conversion to Injection Other Replace on/off & pkr. Dispose Water (Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.) 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\* RU pulling unit, install BOP, release on/off tool, TOH w/ 143 jts. 2 3/8"IPC tbg & on/off tool, found hole in on/off tool, TIH w/ on/off tool & 143 jts 2 3/8" IPC tbg, testing tbg to 5000# (Hydrostatic), on/off tool would not latch. TOH w/ tbg & on/off tool, TIH w/ on/off tool & tbg, strip BOP, NU WH, 06/09/91 press test annulus to 500# for 30 min. held. RD PU, RU Jarrel Service, slick line fish 1.5 plug from Profile nipple, RD Jarrel, started inj. pkr fluid started running out csg valve. SI. TOH w/ pkr, rubber gone, TIH w/ new pkr. set @ 4435.48', test annulus 06/14/91 for 30 min. @ 600 psi, o.k. Put on injection @ 4:15 p.m. Regulatory Secretary 06/25/91 

