

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE  
(Other instructions  
reverse side)Form approved.  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM - 0999A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Mescalero Unit

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Devonian Mescalero W/C

11. SEC., T., R., M., OR BLE. AND  
SURVEY OR AREA

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

Humble Oil &amp; Refining Company

3. ADDRESS OF OPERATOR

Box 2100, Hobbs, New Mexico 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)  
At surface660 FNL, 1980 FEL, Sec. 6, T-19-S, R-34-E  
NW/4 of NE/4 Sec. 6

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3845 DF

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON\*

CHANGE PLANS

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

SUBSEQUENT REPORT OF:

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any  
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Well to be plugged and abandoned. Plugs to be set as follows:

Plug #1 from 14,898 (TD) to 14,800 with 30 sxs cement.  
Plug #2 from 13,100 to 13,000 with 40 sxs cement.  
Plug #3 from 12,270 to 12,170 with 40 sxs cement.  
Plug #4 from 9,100 to 9,000 with 40 sxs cement.  
Plug #5 from 5,250 to 5,150 with 40 sxs cement.  
Plug #6 from 50 to surface with 20 sxs cement.

Mud laden fluid between plugs. Dry hole marker to be installed per N. M. O. C. C. requirements.

The above plugging procedure was verbally approved by the U. S. G. S. through a telephone conversation between Humble's Mr. A. L. Carpenter and Mr. Jack Gordon of the U. S. G. S. on 4-3-64.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Agent

DATE 4-7-64

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

J. L. GORDON

ACTING DISTRICT ENGINEER

\*See Instructions on Reverse Side