	Form Approved,
Form 9-881 a (Feb. 1951)  AP, ROVED (SUBMIT IN TRIP	PLICATE)
List) 2880H.	CE O. C. C. Losso No. NM - 0999A
1 i ! i IMITV Z N 1303	**.** B
J. L. GORDON GEOLOGICAL S ACTING DISTRICT ENGINEER	MESCALERO UNIT
ACTURE MASTER CO.	
SUNDRY NOTICES AND R	EPORTS ON WELLS
NOTICE OF INTESTION TO DIVIDE	QUENT REPORT OF WATER SHUT-OFF
	QUENT REPORT OF SHOOTING OR ACIDIZING
1 1101111111111111111111111111111111111	QUENT REPORT OF RE-DRILLING OR REPAIR.
NOTICE OF INTENTION TO SHOOT OR ACIDIZE	QUENT REPORT OF ABANDONMENT
	ud and cement surface casing X
(INDICATE ABOVE BY CHECK MARK NATURE OF	REPORT, NOTICE, OR OTHER DATA)
	November 18 , 19 6
(NI)	(F).
Well No3 is located660_ ft. from $\begin{bmatrix} N \\ \blacksquare \end{bmatrix}$ lin	ne and $\frac{1980}{1980}$ ft. from $\{$ line of sec
Nw/4 of NE/4 Sec. 6 19-S 34-E (1/4 Sec. and Sec. No.) (Twp.) (Range)	
() Sec. and Sec. No.) (Twp.) (Range)	(Meridian)  New Mexico  (State or Territory)
(% Sec. and Sec. No.) (Twp.) (Range)  Devonian Mescalero W/C Lea  (Field) (County or Subdivision	n) (State or Territory)
The elevation of the derrick floor above sea level is le	ter ft.
DETAILS OF	
(State names of and expected depths to objective sands; show sizes, weights, ing points, and all other impor-	and lengths of proposed casings; indicate mudding jobs, cement-
pudded 18-1/2" hole at 2:30 AM, 11-14-63. H	Ran 352' (11 jts) 13-3/8" casing.
et at 371'. Cemented with 475 sacks Regular	r 4% Gel plus 2% Calcium Chloride.
OB 8:30 PM, 11-14-63. Cement circulated.	WOC 20-1/2 hours. Tested casing with
300# for 15 minutes. No drop in pressure.	Orilled plug at 5:00 PM, 11-15-63.
Prilling.	
I understand that this plan of work must receive approval in writing by	the Geological Survey before operations may be commenced.
Company	y
Address Box 2100	AODY ORIGINAL E O DALLO
Hobbs, New Mexico	By COPY ORIGINAL E. S. DAVIS
	Tal Agent