

IF DRILL-STEM OR OTHER SPECIAL TESTS OR DEVIATION SURVEYS WERE MADE, SUBMIT REPORT ON SEPARATE SHEET AND ATTACH HERETO

TOOLS USED

ROTARY TOOLS WERE USED FROM 0 FEET TO 6280* FEET, AND FROM FEET TO FEET.
CABLE TOOLS WERE USED FROM FEET TO FEET, AND FROM FEET TO FEET.

PRODUCTION

*Driller's Total Depth 64

PUT TO PRODUCING September 5, 1964

OIL WELL, THE PRODUCTION DURING THE FIRST 24 HOURS WAS 29 BARRELS OF LIQUID OF WHICH 31% WAS OIL; % WAS EMULSION; 69% WATER; AND % WAS SEDIMENT. A.P.I. GRAVITY 32.5°

GAS WELL, THE PRODUCTION DURING THE FIRST 24 HOURS WAS M.C.F. PLUS BARRELS OF LIQUID HYDROCARBON. SHUT IN PRESSURE LBS.

LENGTH OF TIME SHUT IN

PLEASE INDICATE BELOW FORMATION TOPS (In Conformance With Geographical Section Of State):

SOUTHEASTERN NEW MEXICO			NORTHWESTERN NEW MEXICO		
T. ANHY			T. DEVONIAN		T. OJO ALAMO
T. SALT			T. SILURIAN		T. KIRTLAND-FRUITLAND
	mustler 1630		T. MONTOYA		T. FARMINGTON
T. YATES	2925		T. SIMPSON		T. PICTURED CLIFFS
T. 7 RIVERS	3102		T. McKEE		T. MENELEE
T. QUEEN	3818		T. ELLENBURGER		T. POINT LOOKOUT
T. GRAYBURG	4197		T. GR. WASH		T. MANCOS
T. SAN ANDRES	4517		T. GRANITE		T. DAKOTA
	Paddock 6130		T.		T. MORRISON
T. DRINKARD			T.		T. PENN
T. TUBBS			T.		T.
T. ABO			T.		T.
T. PENN			T.		T.
T. MISS			T.		T.

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION	FROM	TO	THICKNESS IN FEET	FORMATION
0	148	148	Sand				
148	383	235	Sand and Red Bed				
383	1212	829	Red Bed				
1212	1689	477	Red bed and Anhydrite				
1689	3030	1341	Anhydrite and Salt				
3030	4273	1243	Anhydrite				
4273	6280	2007	Lime				
	T.D.						

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I HEREBY SWEAR OR AFFIRM THAT THE INFORMATION GIVEN HERewith IS A COMPLETE AND CORRECT RECORD OF THE WELL AND ALL WORK DONE ON IT SO FAR AS CAN BE DETERMINED FROM AVAILABLE RECORDS.

October 20, 1964

COMPANY OR OPERATOR Humble Oil & Refining Company ADDRESS Box 2100, Hobbs, New Mexico 88240 (DATE)

NAME COPY ORIGINAL E. S. DAVIS POSITION OR TITLE Agent