

COUNTY	LEA	FIELD	Vacuum	STATE	N.M.
OPR	HUMBLE OIL & REFG. CO.				MAP
	3 New Mexico State "J"				API 30-025-20708
	Sec. 19, T-17-S, R-35-E				CO-ORD
	330' fr S & W Lines of Sec.				
	Spud 7-27-64				
	Comp. 9-11-64				CLASS EL 37982
CSG & SX - TUBING	LOG:	FORMATION	DATUM	FORMATION	DATUM
8 5/8" 1689'	850	Yates 2925			
4 1/2" 4952'	350	7-R 3102			
		Queen 3818			
		Grbg. 4197			
		SA 4517			
		Padd. 6130			
LOGS EL GR RA IND HC A					
		TD 6280', PBD 4943'			

IP San Andres Perfs. 4822-27', Ppd. 9 BO + 20 BW. Pot.
Based on 24 hr. test. Gravity 32.5, GOR TSTM.

Distribution limited and publication prohibited by subscribers' agreement.
Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. DATE PROP DEPTH 6300' TYPE

F.R. 7-30-64.
PD 6300' - Glorieta.
8-3-64 Drlg. 4336' lm.
8-10-64 Drlg. 6091' lm.
8-17-64 TD 6280', PB 4943', prep to test.
DST (Glor) 6128-70', open 1 hr.
Rec. 1705' gas in Drill pipe + 185 G&WCM,
1 hr. ISIP 2129#, FP 60-122#,
2 hr. FSIP 2057#.
Perf. @ 4561', 4569', 4574', 4578', 4586', 4594',
w/1 SPI.
8-24-64 TD 6280', PB 4943', ppg. load.
Ac. 8000 gals. 4561-94'.
Ppd. 2 BLO + 13 BAW/72 hrs.
8-31-64 TD 6280', PB 4943', ppg. load.
Ppd. 2 BLO/24 hrs.
9-8-64 TD 6280', PB 4943', tstg. on pump.
Perf. @ 4822', 4824', 4826', 4827' w/1 SPI.
- cont'd -

LE/ Vacuum N.M. Sec. 19-17S-35E
HUMBLE OIL & REFG. CO. #3 New Mexico State "J" Page #2

9-8-64 - cont'd -
Set Pkr. @ 4764',
Ac. 500 gals. 4822-27'.
Ppd. 10 BO + 20 BW/24 hrs.
9-14-64 TD 6280', PBD 4943', COMPLETED.
Perfs. 4561-94' are packed off.