

COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS <small>(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</small>		5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
		5. State Oil & Gas Lease No. A-1320
1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator EXXON CORPORATION		8. Farm or Lease Name NEW MEXICO "K" STATE
3. Address of Operator P.O. BOX 1600, MIDLAND, TEXAS 79701		9. Well No. 25
4. Location of Well UNIT LETTER J 2310 FEET FROM THE SOUTH LINE AND 1980 FEET FROM THE EAST LINE, SECTION 28 TOWNSHIP 17-S RANGE 35-E N.M.P.M.		10. Field and Pool, or Wildcat VACUUM GLORIETA
15. Elevation (Show whether DF, RT, GR, etc.) 3950' DF.		12. County LEA

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER PERFORATE & STIMULATE <input checked="" type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> CASING TEST AND CEMENT JOBS <input type="checkbox"/> OTHER <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/> PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

PULL RODS AND TBG. PERFORATE INTERVALS 6110-6114', 6118-6120', 6124-6128' WITH 1 SHOT PER FT., USING JET CSG. GUN WITH PREMIUM CHARGE. USE LUBRICATOR WHEN PERFORATING. RUN TREATING PKR. ON WORKSTRING. SPOT ACID FROM 6140-6050' SET PKR. AT 6050'. ACIDIZE PERFORATIONS W/6500 GALS. 15% HCL CONTAINING 7 GALS. COREXIT 7652. PUMP AS FOLLOWS: 1500 GALS. ACID. 400 LB. SLUG OF DIVERTER CONTAINING 200 LBS. BENZOIC ACID FLAKES, 200 LBS. ROCK SALT AND 15 LBS. GUM KARAYA BLENDED INTO 7 BBLs. CLEAN BRINE. 5000 GALS. ACID. 23 BBLs. CLEAN BRINE. DISPLACE ACID INTO FORMATION AT 2-3 BPM RATE NOT EXCEEDING 1200 PSI SURFACE PRESSURE. PULL PACKER. RUN SUBSURFACE PRODUCTION EQUIPMENT AND PUT WELL ON PUMP.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>A. X. Clemmer</u>	TITLE <u>UNIT HEAD</u>	DATE <u>4-6-76</u>
<small>Only Signed by</small> <u>John Sexton</u> <small>APPROVED BY</small>		
<small>CONDITIONS OF APPROVAL, IF ANY:</small>		