

IF DRILL-STEM OR OTHER SPECIAL TESTS OR DEVIATION SURVEYS WERE MADE, SUBMIT REPORT ON SEPARATE SHEET AND ATTACH HERETO

TOOLS USED

ROTARY TOOLS WERE USED FROM 0 FEET TO 6224\* FEET, AND FROM FEET TO FEET.  
CABLE TOOLS WERE USED FROM FEET TO FEET, AND FROM FEET TO FEET.

\*Wire line T. D.

PRODUCTION

PUT TO PRODUCING July 1, 1964

OIL WELL: THE PRODUCTION DURING THE FIRST 5 HOURS WAS 63 BARRELS OF LIQUID OF WHICH 100 %  
WAS OIL, % WAS EMULSION, % WATER, AND % WAS  
SEDIMENT. A.P.I. GRAVITY 37.5

GAS WELL: THE PRODUCTION DURING THE FIRST 24 HOURS WAS M.C.F. PLUS  
BARRELS OF LIQUID HYDROCARBON. SHUT IN PRESSURE LBS.

LENGTH OF TIME SHUT IN

PLEASE INDICATE BELOW FORMATION TOPS (In Conformance With Geographical Section Of State):

SOUTHEASTERN NEW MEXICO

NORTHWESTERN NEW MEXICO

~~Base~~ Rustler 1533  
~~Base~~ Base salt 2663  
~~Base~~ Tansill 2715  
T. YATES 2817  
T. 7 RIVERS 3052  
T. QUEEN 3697  
T. GRAYBURG 4068  
T. SAN ANDRES 4367  
T. GLORIETA 5921  
~~Base~~ Paddock Pay 6073  
T. TUBBS  
T. ABO  
T. PENN  
T. MISS

T. DEVONIAN  
T. SILURIAN  
T. MONTOYA  
T. SIMPSON  
T. MCKEE  
T. ELLENBURGER  
T. GR. WASH  
T. GRANITE  
T.  
T.  
T.  
T.  
T.

T. OJO ALAMO  
T. KIRTLAND-FRUITLAND  
T. FARMINGTON  
T. PICTURED CLIFFS  
T. MENELEE  
T. POINT LOOKOUT  
T. MANCOS  
T. DAKOTA  
T. MORRISON  
T. PENN  
T.  
T.  
T.  
T.  
T.

FORMATION RECORD

FROM	TO	THICKNESS IN FEET	FORMATION	FROM	TO	THICKNESS IN FEET	FORMATION
0	1132	1132	Red Bed				
1132	1583	451	Anhydrite				
1583	2850	1267	Salt and Anhydrite				
2850	6224	3374	Lime				
	T. D.						

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I HEREBY SWEAR OR AFFIRM THAT THE INFORMATION GIVEN HERewith IS A COMPLETE AND CORRECT RECORD OF THE WELL AND ALL WORK DONE ON IT SO FAR AS CAN BE DETERMINED FROM AVAILABLE RECORDS.

August 28, 1964

(DATE)

COMPANY OR OPERATOR Humble Oil & Refining Company

ADDRESS Box 2100, Hobbs, New Mexico

NAME COPY ORIGINAL SIGNED E. S. DAVIS

POSITION OR TITLE Agent