STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

WO, OF COPIED DECEIVED		
DISTRIBUTION	-	
SANTA FE	7	
FILE		
U.1.0.1.		
LAND OFFICE	1	
OPERATOR	 	_

CONDITIONS OF APPROVAL, IF ANY!

JIL CONSERVATION DIVISIO. P. O. BOX 2088

Form C-103 . Revised 10-1-78

SANTA FE, NEW MEXICO 87501	
U.S.O.S.	5a. Indicate Type of Leuse
DERATOR	State X Fon
LOTERAL DA	5. State Oil & Gus Leuse No. 387
SUNDRY NOTICES AND REPORTS ON WELLS 100 NOT USE THIS FORM FOR PROPOSALS TO TRILL OR TO DEEPLN OR PLUG BACA TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT _" IFORM C-101) FOR SUCH PROPOSALS.]	
1. OIL X GAS OTHER. Re-enter to replug	7. Unit Agreement Name
2. Name of Operator	8. Farm or Lease Name
*Marathon Oil Company J. Address of Operator	Warn State A/C #4
Room 401, 4001 Penbrook, Odessa, Tx. 79762	9. Well No. 1
4. Location of Well	10. Field and Pool, or Wildcat
UNIT LETTER M , 330 PEET FROM THE SOUTH LINE AND 330 PEET FROM	Undesignated Glorieta
THE West LINE, SECTION 23 TOWNSHIP 17-S NAME 35-E NMPM.	
15. Elevation (Show whether DF, RT, GR, etc.)	12. County
3923' GR	Lea
Check Appropriate Box To Indicate Nature of Notice, Report or Oth NOTICE OF INTENTION TO: SUBSEQUENT	
PERFORM PEMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
PULL OR ALTER CASING CHANGE PLANS CASING TEST AND CEMENT JOB	PLUG AND ABANDONMENT
OTHER Replugged per OCD *Phillips Petroleum Compa	
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including e work) SEE RULE 1703. (originally P & A by Marathon Oil 6-5-64)	stimated date of starting any proposed
07-15-80 - MI well Units WS. Cleaned out from surface to 1530'.	
<u>07-16/17-80</u> - Cleaned out to 4300'.	
<u>07-18/20-80</u> - Spotted 145 sxs. Cl. "C" cmt. @ 4300' & 75 sxs at 2850'. 2740'. Plugged tbg. to 1820', spotted 100 sxs Cl. "C" cmt 7-20-80 - crew off.	Tagged cmt. plug Pulled tbg.
O7-21-80 - Tagged cmt. plug at 1000'. Spotted 30 sxs Cl. "C" cmt. @ 400 and filled 8-5/8" csg. to surf. MO well units. Installed dr. P & A.	o', 100 sxs at 100', ry hole marker. Well
BOP equipment series 900 - 3000 V WP double w/l set blind rams and l set	pipe rams (Mann.oper.)
6. I hereby certify that the information above is true and complete to the best of my knowledge and belief.	
Phillips Petroleum Company W. J. Mueller Senior Engineering Specialis	t July 23, 1980
	1110.0
ONDITIONS OF APPROVAL, IF ANY:	<u>AUG 8 1983</u>