

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-85

3a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.
B-2317

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO RE-ENTER OR PLUG BACK TO A DIFFERENT RESERVOIR. SEE APPLICATION FOR PERMIT TO DRILL FORM C-101 FOR SUCH PROPOSALS.)

OIL WELL ☐	GAS WELL ☐	OTHER- BHP Monitoring Well	7. Unit Agreement Name
Name of Operator Phillips Petroleum Company			8. Farm or Lease Name H. E. Hale
Address of Operator Room 806, Phillips Building, Odessa, Texas 79761			9. Well No. 9
Location of Well UNIT LETTER J 1785 FEET FROM THE East LINE AND 1980 FEET FROM THE South LINE, SECTION 35 TOWNSHIP 17-S RANGE 34-E			10. Field and Foot, or Wildcat Vacuum (Gh-San Andres)
15. Elevation (Show whether DF, RT, GR, etc.) 4013' GR 4026' PKB			12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	
		OTHER Perforate San Andres for BHP monitor ☒	
		Purposes	

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

(2-8-78)

MI Johnson WS unit. Ran 2-3/8" tbg to 4700'. Displaced water in hole w/oil. Runco spotted 300 gals 10% acetic acid on bottom. Pulled 2-3/8" tbg. Well shutdown prior to workover.

(2-9-78)

Swbg; Ran Guns perf'd 7" csg w/2 jet shots per foot, 4610'-4624', 4632-4654'. Ran 2-3/8" tbg & Baker Lokset plm, set plm at 4580'. Swbd 2 hrs, 18 BLO, swbd dry. Runco treated down tubing thru csg perfs 4610-4654' w/2000 gals 20% HCl acid w/2 ball sealers per bbl last 1500 gals. Flushed w/22 EO. Max press 2300#, min 2000#, inst SDP 200#, vacuum in 1 min. Inj rate 3.4 BPH. Swbd 2 hrs, 20 BLO. Single coil in Vacuum (Grayburg-San Andres) Field. SI for BHP monitoring.

(2-19-78)

BHP 574#

(2-20-78)

BHP 574#

(2-21-78)

BHP 574#

BOP: Series 900, 3000# WK, double w/one set pipe rams, one set blind rams.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *[Signature]* TITLE Engineering Advisor DATE March 3, 1978

APPROVED BY *[Signature]* TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

U.S. COAST & GEOD. SURV.
U.S. COAST & GEOD. SURV.
U.S. COAST & GEOD. SURV.