NEW MEXICO OIL CONSERVATION COMMISSION

DISTRIBUTION						
SANTA FF						
FILE						
U.S.G.S.	-					
LAND OFFICE						
	OIL					
TRANSPORTER	GAS					
PRORATION OFFI	E					
OPERATOR						

12-1/4

7-7/8

8-5/8

4-1/2

1713'

62501

750

800

Santa Fe, New Mexico

WELL RECORD

	•						
. (7.						
G	4						
1							

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE

If State Land submit 6 Copies

AREA 640 ACRES Santa Fe Phillips Petroleum Company (Company or Operator) .¼, of Sec. 26 , T. 178 , R. 35E , NMPM in MW 14 of NW 94 (Paddock) Pool Lea Undesignated line and 335 feet from west feet from north ... If State Land the Oil and Gas Lease No. is. B-1497 26 3-5-64 , 19 Drilling was Completed 3-19-64 , 19 Drilling Commenced..... Phillips Petroleum Company Fig No. 30 Name of Drilling Contractor..... Bartlesville, Oklahoma Elevation above sea level at Top of Tubing Head 3921 GL The information given is to be kept confidential until OIL SANDS OR ZONES 6148 6132 IMPORTANT WATER SANDS Include data on rate of water inflow and elevation to which water rose in hole. No. 1, from..... CASING BECORD KIND OF CUT AND PULLED FROM NEW OR USED WEIGHT PER FOOT PURPOSE PERFORATIONS SIZE AMOUNT 1698 Hallib Surface 8-5/8" 24# New 6132-6148 6138 Ħ Production 9.5,10.5# 4-1/2" New MUDDING AND CEMENTING RECORD METHOD USED MUD GRAVITY AMOUNT OF MUD USED NO. SACKS WHERE SET SIZE OF HOLE SIZE OF

Pump-plug

RECORD OF PRODUCTION AND STIMULATION					
(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.) Acidised with 3000 gallons reguar 15% acid					

	•				
	•••••				

ion Stimulation Flowed 24 hours, 236 barrels oil, no water.

Depth Cleaned Out...

RECORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

	toois wer	used from	, suriace	feet to	D (6250)	feet,	, and fron	a	feet to	fret
Cable to	ools were	used from.	•••••	feet to		feet,	and fron	ı	feet to	fcet
					PROL	UCTION				
Put to	Producing	Maj	rch 25, 1964		, 19					
OIL W							1	h1 6.1	iquid of which. 99.8	
	T.	vas oil:	• "					carreis of I	iquid of which	% was
			37 .0	was emu	sion;	.	% wa	ter; and	% was sec	diment. A.P.I.
			37. 0							
GAS W	ELL: T	he product	ion during the first	24 hours	was		M.C.F.	plus		barrels of
			carbon. Shut in Pi							on the state of
Length	of Time	Shut in								
		<u>-</u>	Southeastern	New Mexi	rs (IN CO)	NFORMA	NCE WI	TH GEOG	RAPHICAL SECTION OF	
T. Anh	y	16	45		vonian			T.	Northwestern New M	
					urian				- j	
				T. M	ontoya					
			•••••••••••••••••••••••••••••••••••••••	T. Sir	npson					
T. 7 Ri T. Oue	vers	27	40		Kee				Menefee	
T. Grav	burg	40	15		enburger				Point Lookout	
T. San	Andres	43	66		Wash				Mancos	
T. Glor	ieta	59	84	T.					Dakota	
			6130	Т	••••••••				Morrison	
				T	••					
								т.		
			***************************************		••••••					
					ORMATIO			т.		••••••••
-		Thickness				TO RECC	 			
From	То	in Feet	Fo	rmation		From	То	Thicknes in Feet	Formation	
1006	1006	1006	Redbed							
3170	3170 3650	2164 480	Redbed, an Anhydrite,	hydrite lima	1					
3650	4031	381	Lime							
4031 4239	4239 5121	206 682	Lime, sand							
5121	6250	1129	Lime, idolor Dolomite,							
	TD	-							r	
1					1					
	i									
J	,									

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is as can be determined from available records.	a complete and correct record of the well and all work done on it so far
	165 Conton March 26, 196
Company or Operator Phillips Petroleum Company	Address Box 2130 - Hobbs, New Mexico